## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For parago in	Filing Require	ement of Act 74, Mich. F	P.A. 1970		
For corners in Presque Isle (County)	Located In:	Corner Code ##	PRI	ESQUE ISLE COL RECORDED	YTA
Public Land Survey	T 34N R 5E T R R T R T R R T R R T R R T R T R R T	A-10	96 JUN-4 AMII: 24  Zenet M. Lamb		
Property Controlling     in Section	S T R S T R	<del></del>	• 1	REGISTER OF DEE	D\$
3. Miscellaneous	S T R		Register of D	Deeds Stamp & File	e Number
Property in Sec.	S R	(			
4. Lot No , Rec	corded Plat		А В		I J K L M
5. Private Claims				CDEFGH	I J K L M
7			3 - 6-	5-4-3-	1-2-1-1-1
Norman J. Quaine	in a field supply on Decem	ber 11, 1996a	4 7-	+ 8-+ 91'0- 	11-1-12-1
do hereby certify that under requi in lines 1 and 2 above were in a current manual of survey instruc Management or by a decree of a C above were in conformance with Court of Law; established, re- expressed below:	rements of P.A. 74, Michigan P.A. conformance with regulations an tions of the United States Depart out of Lawand/or that the corne the rules of the Michigan Board of the tions.	of 1970, the corner points ment of rules therefore as required tment of the Interior, Bureau o er points mentioned in lines 3, 4 of Land Surveyors or by a Decre	ioned 6 18—18—18—19—19—19—19—19—19—19—19—19—19—19—19—19—	20 21 -22 -29 -28 -27	23 24
NOTE: Not more than 4 cor on this certificate.	ners, all in the same town a	nd range, may be recorded	11 12 31-	32 33 34	35 36
A. Description of original me	onument and accessories and	d/or subsequent restoration			
A-10 1840 Township lines ru by John Hodgson Deputy Surveyor Hemlock 11 S18W 1 Do 8 N19E 17	by Alfred Mil Deputy Survey	or mship corners corner J 54			
B. Description of corner evi	dence found and/or method	applied in restoring or rees	tablishing corner:		
A-10 December 11, 1996 Norman J. Quaine P.S.#33984, Porte Survey P.C. 1996 P.I. Co. Sta Remonumentation	Set 1/2" Rod r's section corne 3' E of Road		line with		
<ul><li>Description of monument</li><li>A~10</li></ul>	for corner and accessories	established to perpetuate I	ocating the position	n of the corner:	
Left 1/2" Rod & Cap #33984 S80° E 66.20' 7" Maple N85° W 52.65' FE Cor. N41° E 55.12' 3" W. Pine N52° E 49.36' 4" Tamarack		in a	Ratified by Peer Group in accordance with P.A. 345 Chairman		
*Witness	tags & nails.	Dat .	e <u>5/22 /9</u>	<u> </u>	
Porter's Survey P	.c./A		May 20	100%	•
Signed by Assman	y maine	Date	14HY 24	/776	
Surveyor's Michigan License	No. 33.989		FORM APPROVED BY MICHE	GAN STATE BOARD OF LAND SU	RVEYORS, JAN. 26, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983