

1269

1996 PRESQUE ISLE COUNTY, STATE OF MICHIGAN REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Presque Isle
(County)

Located in:

Corner Code #

1. Public Land Survey

T 34N R 5E F-13
T R
T R
T R
S T R
S T R
S T R
S T R

2. Property Controlling in Section

3. Miscellaneous Property in Sec.

LIBER 319 PAGE 116

PRESQUE ISLE COUNTY
RECORDED

96 JUL 12 AM 11:39

Janet M. Lambert
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, James A. Beck, in a field survey on Mar 12, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Grid table with columns A-M and rows 1-13. Contains numbers 1-36 and a circled 0 in row 12, column G.

A. Description of original monument and accessories and/or subsequent restoration:

F-13
"Set 1/4 Sec. post"
G.L.O. 1840 Hemlock 7, N71W 20
John Hodgson Cedar 12, N67E 12

Aug. 17, 1979 1/2" Rod Cor recorded in
P.A. 74 Recordation Witnesses: T33N, R5E ( Metz Twp.)
by Ronald Bischer N14°W 51.12' Power Pole R. Bischer set "in line
Reg. No. 22428 S03°W 32.44' Fe. Cor with fence to South
S 46°W 60.85' 7" Aspen in Centerline Road "

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-13
1996 Remonumentation found 1/2" iron with 15410 cap in monument box
by James A. Beck
P.S. 21559
Witnesses:
N 14°W 51.07' (measured) 15410 tag in power pole
S 3°W 32.44' fence corner down
S 46°W 60.85' 11" Aspen

Ratified by Peer Group
in accordance with P.A. 345
Date 5/22/96

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-13
1996 Remonumentation 1/2" iron with 15410 cap in monument box
by James A. Beck
P.S. 21559
Witnesses:
N 14°W 51.07' (measured) 15410 tag in power pole
S 3°W 32.44' fence corner down
S 46°W 60.85' P.S. 21559 tag in 11" Aspen
S 56°W 67.27' P.S. 21559 tag in 11" poplar
N 81°E 216.37' P.S. 21559 tag in power pole



Signed by James A. Beck
Surveyor's Michigan License No. 21559

Date June 17, 1996