

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
PRESQUE ISLE
(County)

Located In:

Corner Code ~~==~~

- | | | |
|------------------------------------|------------|-----------|
| 1. Public Land Survey | T 35N R 3E | J-5, K-4, |
| | T R | K-5 |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S 11 T R | 16 |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CARL F. ROSER, in a field survey on JUNE 7, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-5	K-4	K-5
-----	-----	-----

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- | | | | |
|---|--|---|--|
| J-5 | K-4 | K-5 | 16 |
| REESTAB S 1/4 COR OF SEC 11
EQUIDISTANT AND ON LINE BETW
FD SE & SW COR'S OF SEC 11.
CTR OF N-S TRAIL ROAD IS 25.7'
WEST. | FD AND ACCEPTED 1/2" ROD
W/P.S. #22428 CAP, RON
BISCHER, FOR E 1/4 COR OF
SEC 11. | ACCEPTED 1 1/2" - 2" PIPE (AS
NOTED BELOW) FOR SE COR OF
SEC 11. CORNER PREVIOUSLY WIT
& USED BY OTHERS. | ESTAB SE COR OF SW 1/4 OF
SE 1/4 OF SEC 11 PER STD BLM
INSTRUCTIONS. COR FALLS IN
CTR OF E-W TRAIL RD. CTR OF
CO RD (ESE & MNW) IS 69'
SOUTH. |

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | | |
|---|---|--|---|
| J-5 | K-4 | K-5 | 16 |
| SET STD DNR MON & RED TOP CED
POST. LG NAILS W/BRASS TAGS
ON WITS.
16" & 20" TW OAK N46°W 64.98'
10" W PINE S47°E 4.21'
5" J PINE S59°W 64.42'
5" MAPLE N10°E 31.62'
CTR OF N-S RD OVER
CULVERT N10°W 88' | FD 1/2" IR ROD W/BISCHER CAP
#22428 & SET CED POST W/LOC
TAG
LG NAILS W/BRASS TAGS ON WITS.
#12" W PINE N77°W 32.84'
#8" R PINE N74°E 24.83'
8" R PINE S29°E 14.74'
#28" R PINE S04°E 31.62'
SOLD WIT POSSIBLY R. BISCHER | FD 1 3/4" IP IN RD. INTERS.
LG NAILS & BRASS TAGS ON WITS.
#12" R PINE N68°W 43.41'
#24" R PINE N68°E 46.31'
#20" R PINE S82°E 52.27'
4" W PINE S28°W 27.91'
CORNER IS 2' S OF CTR E-W
TRAIL AND IN CTR TRAIL TO S.
SOLD WIT POSSIBLY RON BISCHER. | SET 5/8" X 30" REROD W/CAP. LG
NAILS W/BRASS TAGS & BLAZES ON
WITS.
SET RED TOP
CEDAR POST N08°E 11.5'
6" MAPLE N23°E 21.47'
4" R PINE S17°E 21.29'
30" OAK S13°W 18.08' |

Signed by Carl F. Roser Date 6-08-95

Surveyor's Michigan License No. 12028