

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Presque Isle
(County)

Located In

Corner Code #

1. Public Land Survey T _____ R _____
T _____ R _____
2. Property Controlling
in Section S 16 T 35N R 2E 4
S 16 T 35N R 2E 5
3. Miscellaneous
Property in Section S _____ T _____ R _____
S _____ T _____ R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on December 14, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8			9		10		11		12	
5													
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

4 – NW 1/16 Corner, Section 16, T35N, R02E

5 – CN 1/16 Corner Section 16, T35N, R02E

This corner was not set during the original survey.

This corner was not set during the original survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

4 – NW 1/16 Corner, Section 16, T35N, R02E

5 – CN 1/16 Corner Section 16, T35N, R02E

Set a stamped 2" dia. aluminum cap on 5/8"x32" rerod per standard BLM procedure for subdivision of a section.

Set a stamped 2" dia. aluminum cap on 5/8"x32" rerod per standard BLM procedure for subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4 – NW 1/16 Corner, Section 16, T35N, R02E

5 – CN 1/16 Corner Section 16, T35N, R02E

stamped 2" dia. aluminum cap on 5/8"x32" rerod

stamped 2" dia. aluminum cap on 5/8"x32" rerod

Wit: N48°E 11.75' to set N&T on SE side 7" W. Pine
S50°E 69.05' to set N&T on E side P. Pole
S38°W 19.40' to set N&T on W side 6" W. Pine
N87°W 10.68' to set N&T on N side 4" W. Pine

Wit: S67°E 6.20' to set N&T on S side 16" W. Pine
S37°E 19.61' to set N&T on N side 13" W. Pine
N78°W 19.33' to set N&T on S side 7" W. Pine
N34°W 7.39' to set N&T on SW side 18" W. Pine
S37°W 2.23' to found 1/2" rod W/ PS Cap#22428

Set Blue Carsonite Post w/ location tag 1' North

Set Blue Carsonite Post w/ location tag 36' East

Carl T. Kiiskila

Surveyor's Michigan License No.: 33981

4-24-12

