\_\_\_ , Recorded Plat \_\_

1995 PRESQUE ISLE COUNTY, STATE OF MICHIGAN REMONUMENTATION

## JAN 1 7 1996 LAND CORNER RECORDATION CERTIFICATE

LIBER 316 PAGE 274

For corners in	COMMISSION Requirement of Act 74, Mich. P.A. 19
or corners in	COMMISSION


PRESQUE ISLE COUNTY RECORDED

Presque Isle	Located In:	Corner Code ##
Public Land Survey	T 36N R 2E	A-4
	T R	
	T R	
	T	
2. Property Controlling	S T R	
in Section	S T R	
3. Miscellaneous	S	
Property in Sec.	S T R	

95 OCT 20 PH 4: 23

Register of Deeds Stamp & File Number

_ Norman J. Quain⊖n a field survey on _	March 31	<sub>19</sub> 95			
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land					
Management or by a decree of a Court of Law and/or that above were in conformance with the rules of the Michig Court of Law, established, re-established, monume	t the corner points an Board of Land	s mentioned in lines 3, 4 and 5 Surveyors or by a Decree of a			



NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

A-4GLO Notes

expressed below:

Lot No.

Private Claims \_

Resurvey 1856

Y. Pine 13" N57°W 52 W. Pine 14" S30°W 38

George H. Cannon

11-6-78

Presque Isle County

Local Remonumentation

LCRC Page 340 Delmer E. Porter

#15410

Fd. 3" Pipe

Replaced w/conc mon/brass cap

N23°W 74.11' 9" N. Pine S33°W 54.46' 12" N. Pine

S70°E 34.70' P. Pole

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-4

March 31, 1995

Presque Isle County

State Remonumentation

Norman J. Quaine

#33984

Fd. conc Mon

Brass Cap was gone

N20°W 73.66' 14" N. Pine S68°E 34.89' P. Pole

S36°W 54.55' 16" N. Pine

Porter's Survey P.C.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Left conc Mon

N20°W 73.66' 14" N. Pine

N48° E 60.57' 10" Oak S68° E 34.89' P. Pole

S36°W 54.55' 16" N. Pine

Ratified by Peer Group in accordance with P.A. 345 Chairman Jelm

\*Witness tags & nails used.

Surveyor's Michigan License No.

Date OCTOBER