

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. <u>36</u> N. R. <u>3</u> E.		<u>K-12; J-11; J-12</u>
2. PROPERTY CONTROLL- ING IN SECTION_____ T. _____ N. S. R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION_____ T. _____ N. S. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 11, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
C. CONTINUED

J-12
SET 5/8" ROD W/RLS CAP
14" R. OAK N70°E 35.0'
12" R. OAK S47°E 65.0'
CEDAR POST EAST 30'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-12 - SET CORNER BY PROPORTIONATE MEASUREMENT, MIDPOINT ON LINE, BETWEEN SECTION CORNERS. COULD LOCATE NO PREVIOUS CORNERS.
J-11 - SET CORNER BY SINGLE PROPORTIONATE MEASUREMENT, MIDPOINT ON LINE BETWEEN SECTION CORNERS. NO PREVIOUS CORNER FOUND.
J-12 - SET CORNER BY STANDARD SURVEY PROCEDURE, AT THE CALCULATED INTERSECTION OF THE TRUE 1/4 LINES.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12
SET DNR MONUMENT - BELOW SURFACE
10" R. OAK S65°E 20.2'
4" R. PINE N34°W 35.3'
CEDAR POST EAST 2'

J-11
SET DNR MONUMENT (BURIED IN ROAD)
12" J. PINE N23°W 19.8'
7" J. PINE N68°W 40.5'
SET 4" CEDAR POST W/LOCATION TAG
10FT N. OF CORNER

SIGNED BY Kenneth J. Ostling DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

PRESQUE ISLE

