

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Presque Isle

Located In

Corner Code #

(County)

1. Public Land Survey	T	36N	R	3E	C-8
	T	36N	R	3E	C-9
2. Property Controlling in Section	S		T		R
	S		T		R
3. Miscellaneous Property in Section	S		T		R
	S		T		R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on March 24, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-8 G.L.O. G.H. Cannon 1854 set quarter section post  
Wit: Spruce Pine 7" S70°E 36 links  
Spruce Pine 5" N35°W 12 links

C-9 G.L.O. G.H. Cannon 1854 set post corner of sections  
19,20,29,and 30  
Wit: W. Pine 17" S62.5°W 33.5 links  
Hemlock 10" N53°E 31 links

Liber 1, Page 99 Larry G. Beauregard P.S. #18654 Found 1"  
pipe 50' west of the centerline of a county road.  
Wit: S30°W 16.00' 8" J. Pine  
N55°W 24.31' 6" J. Pine  
East 10.19' 10" J. Pine

Liber 316, Page 485 Norman J. Quaine P.S. #33984 found  
a 1 5/8" pipe and 4" X 4" scribed stake for corner.  
Wit: N87°W 9.19' 6" W. Pine  
N35°E 7.15' 5" Maple  
S43°E 35.57' 6" Maple  
S24°E 7.07' 10" W. Pine

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

C-8 Found a 1" X 5.5' pipe bent from snow plowing.  
Removed 1" pipe and replaced with a new 1" X 48" pipe with  
P.S. cap #33981 in existing position.

C-9 Found a 1 1/2" pipe as witnessed by N.J. Quaine.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-8 1" X 48" pipe with P.S. cap #33981  
Wit: 8" J. Pine N50°E 28.33'  
8" J. Pine N15°W 29.30'  
5" Twin J. Pine N55°W 24.40'  
10" J. Pine N42°W 15.57'

C-9 1 1/2" pipe  
Wit: 14" W. Pine S27°E 7.45'  
9" W. Pine N85°W 9.03'  
6" Maple Clump N49°E 7.15'  
6" Maple Clump S45°E 35.64'

Signed by:

*Carl T. Kiiskila*

Date:

6-29-04

Surveyor's Michigan License No.:

33981

