

3897

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich P.A. 1970

For corners in
 Roscommon County

Located in:

Corner Code #

1. Public Land Survey

T22N	R3W	G-13
T21N	R3W	G-1 ✓
T	R	
T	R	

STATE OF MICHIGAN
 ROSCOMMON COUNTY
 RECORDED

19 MAY 98 11:09 A.M.

ROBERT W. SMITH
 REGISTER OF DEEDS

I, Larry L. Cavanagh, in a field survey April, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

FILE IN LIBER 3 OF LAND CORNERS
 Register of Deeds Stamp & File Number

A. Description of original monument and accessories and/or subsequent restoration:

JOHN BRINK 1838
 SET POST CORNER
 YELLOW PINE 10 N56°E 38'
 YELLOW PINE 12 N26°W 59'

LCRC L2, P249 1970'S
 CONC. MON.
 24' R. PINE N70°E 98.40'
 8' R. PINE S61°E 63.95'
 12" OAK S68°E 84.17'

WILLIAM A BURT 1850
 W. PINE 16 S53°W 21'
 W. PINE 12 S45°E 19'

C. EUGENE OSTLING LCRC 1971
 L2, P21
 CONC. MON.

DNR 1930'S
 ESTABLISHED CORNER
 N.B.T.
 W. PINE STUMP 36 N6°W 33'

24' R. PINE N70°29'E 98.4'
 8' R. PINE S61°09'E 63.95'
 12" OAK S68°20'E 84.17'

SCHAAF INDICATES IRON
 SET

C. EUGENE OSTLING 12026 1971
 CONC. MON.
 SAME WITNESSES AS ABOVE

C. EUGENE OSTLING 12026 1975
 L305 P688
 NO WITNESSES

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	18	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" X 18" STEEL BAR OVER 4"X3" CONC PLAT MON

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET STANDARD ROSCOMMON COUNTY MONUMENT STAMPED 17614
 WIT: NAIL & TAG IN 12" B. OAK N37°W 60.55'
 NAIL & TAG IN 18" NORWAY N07°E 71.51'
 NAIL & TAG IN 24" NORWAY N70°E 98.48'
 NAIL & TAG IN 13" W. PINE S48°E 33.78'
 NAIL & TAG IN 6" J. PINE S65°W 78.29'
 CARSONITE POST S30°W 28.0'

**SURVEY &
 REMONUMENTATION**

THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

OCT 05 1998

SECTION

ROSCOMMON COUNTY

PEER GROUP APPROVAL

DATE

Marvin E. Myers
 Marvin E. Myers, P.S.

County Surveyor



Signed by *Larry L. Cavanagh*
 Surveyor's Michigan License No. 17614

Date

May 16, 1998

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN., 1983

LIBER 3 PAGE 508