

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Roscommon
(County)

Located In Corner Code #

1. Public Land Survey	T	22N	R	2W	B-12		
	T		R				
2. Property Controlling in Section	S	31	T	22N	R	2W	9
	S		T		R		
3. Miscellaneous Property in Section	S		T		R		
	S		T		R		

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 15, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

B-12 This corner was not established during the original Government survey.

9- This corner was not established during the original Government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

B-12 Established the center of section at the intersection of the East-West and North-South quarter lines as per B.L.M. instructions for the subdivision of a section.

9- Established the Northwest corner of the Northeast quarter of the Southeast quarter of section 9 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-12 Set 5/8" X 32" Capped iron rod with P.S. Cap #33981
Wit: Set nail and tag in South side of a 20" Red Oak N83°W 58.93'
Set nail and tag in West side of a 6" Balsam N05°W 25.84'
Set nail and tag in South side of a 17" Red Pine S80°E 31.25'
Set nail and tag in Southeast side of a 16" Red Pine S10°W 35.65'
Carsonite Post North 1'±

9- Set 1" X 48" pipe with P.S. cap #33981
Wit: Nail and tag in East side of a 2" W. Pine S04°W 45.37'
Nail and tag in Southwest side of a 4" Red Pine S53°W 59.43'
Nail and tag in South side of a 5" Balsam N67°E 70.23'
Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

2-6-08

Surveyor's Michigan License No.:

33981

