## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Roscommon		Locate	d In	Corner Code #	8				
(County)									
1. Public Land Survey		T 22N T 22N	R 3W 3W	H-9			20		
Property Controlling in Section	s	T ===	R						
Miscellaneous     Property in Section	ss	T	- ``—— R R		į	Register	of Deeds Star	np & File	Number
4. Lot No:	Recorde	ed Plat:			. ,A	BCD	E F G H	l J	K L M
5. Private Claims: _		22			. 2	6 - 5 -	4 3		T-1
I, Carl T. Kiiskila, in a fiel					3 -	7 8	9 10	11-	12

and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A E	3 0	D	E I	F G	н	l J	K L	. м
1						$\neg \Box$	TT	T	
2	<u>—</u> е	<u>i</u> —	<u> </u>	<b>-</b>	<u> </u>	- 3	<del> </del> − į-	- 1	:⊢
3	_	H	-	+	$\vdash$		$\vdash$	+	$\vdash$
4	7	!—		9	<del> </del>	-10	<del> -</del> -1 -	┼1	<u> </u>
5	<del> </del>	<del> </del>			$\vdash$	+	╂═┼	_	Н
6	1	 	—17·	1	ļ 6——	-16—	-1,4-	<b>-</b> ↓-1	3—
7	$\vdash$	<u> </u>		$\perp$	$\sqcup$		$\downarrow \downarrow$		Ш
8	_1	 <del>9</del> —	20_	2		-22—	23-	_ 2	
9		L	Н	_	$\vdash$	<del>-</del>	++	+	
10	<b>—</b> 3	ļ—	29·	<del></del> 2	<u> </u>	-27	26	<u>2</u>	5—
11	$\vdash$		$\vdash$	-		- -	<del>   </del>	_	$\vdash\vdash$
12	-3	<u> </u> -	32	3	3-	-34	35	<del></del> 3	[ 6
13	Ц.	<u> </u>							

A. Description of original monument and accessories and/or subsequent restoration:

H-9 - 1/4 Corner comm. to sec.'s 22 & 27, T22N,R3W

2005 - Remon L.C.R.C. - L.3, p.1050 - Marvin E. Myers, P.S. #31600 - Set standard county monument in box after road construction.

Nail and tag 15" W. Oak N22°W 56.55' Nail and tag 18" W. Oak N22°E 45.45' Nail and tag 9" Maple S30°W 56.23' Nail and tag 4" W. Pine S37°E 56.30"

I-11 - Section corner comm. to sec.'s 26,27,34,35, T22N,R3W

1849 - GLO - William Burt - Set Pine Post. Spruce 5" S18°W 1.80 ch

S. Pine 8" N01°E 2.69 ch

1962 - Survey Map - George D. Henning, P.S.#2240 - Fd. pipe. 6" J. Pine N48°W 13.2'; 8" J. Pine S57°W 13.5'; 8" J. Pine

1970's - L.C.R.C. - L.2, p.250 (prior to Act. 74) - Same info as Survey Map by Henning.

1974 - Survey Map of Sec. 35, T22N,R3W - Larry L. Cavanagh, P.S.#17614 - Found pipe and references 1962 Henning. Same witnesses.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-9 - 1/4 Corner comm. to sec.'s 22 & 27, T22N,R3W

Found Roscommon County monument in monument box in centerline of E-W paved road per L.C.R.C., L.3, p.1050. Two of the witnesses were missing; so reason for re-witnessing comer.

I-11 - Section corner comm. to sec.'s 26,27,34,35, T22N,R3W

Found 2" pipe 8" below water in swamp with metal collar lying next to pipe. Accepted found pipe as the best available evidence for the position of the original corner. Drove 1" dia. x 48" long galvanized pipe inside found 2" pipe and placed standard 4" dia. aluminum stamped DNR cap on pipe. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-9 - 1/4 Corner comm. to sec.'s 22 & 27, T22N,R3W

I-11 - Section corner comm. to sec.'s 26,27,34,35, T22N,R3W

Standard Roscommon County monument in mon. box

Wit: N12°E 61.41' to set N&T on W side 14" W. Oak \*S46°E 56.27' to set N&T at old N&T on NE side 6" W. Pine \*S23°W 56.17' to fd. N&T on NW side 10" R. Maple \*N28°W 56.56' to fd. N&T on W side 19" W. Oak

Found Orange Carsonite post 33.6' North

\* Previous recorded witness.

4" dia. alum. cap on 1"x48" galv. pipe driven in 2" dia. pipe

Wit: N77°E 26.49' to set N&T on N side 3" J. Pine S07°E 31.87' to set N&T on W side 4" W. Pine S64°W 40.59' to set N&T on S side 3" Twin W. Pine N25°W 30.20' to set N&T on E side 4" W. Pine \*N68°E 19.87' to fd. nail & washer on W side 7" dead J.Pine \*S57°W 13.41' to fd. nail & washer on E side 7" dead J.Pine Set Blue Carsonite post 1' North

Surveyor's Michigan License No.:

33981

T Kusk

Previous fred of the witness. CARL -12 -KIISKILA 本 LAND SURVEYOR No. FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 28, 1971
Revised May 14, 1975

LAND

Revised May 14, 1975 Revised Jan. 1983

Revised Oct. 1995