SURVEY & REMONUMENTATION

5756

MAY 28 1997

COMMISSAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

5	Filing Require	ement of Act /4, Mich. P.A.	. 1970
For corners in		1	
Roscommon	Located In:	Corner Code ##	STATE OF KICHIGAN
(County)			ROSCOMMON COUNTY
	T 22N R 3W	(A-6)/	RECORDED
 Public Land Survey 	7 22N R 4W	M-6	A Train of Section 20.
	· 		15 AUG 96 10:47 A.M.
	T R		TO UND AN TA-A: DRUE
	T R		ROBERT W. SHITH
2. Property Controlling	S T R		REGISTER OF DEEDS
in Section	S T R		
3. Miscellaneous	s T R		Register of Deeds Stamp & File Number
Property in Sec.	S T R		
4. Lot No ,	Recorded Plat		A B C D E F G H I J K L M
5. Private Claims			
•			3
•			
	.	1.4 05	9-10-11-12-
, J. Dean Geers	_ , in a field survey on	, 19 73	5
do nereby certify that under r	requirements of P.A. 74, Michigan P.A.	of 1970, the corner points mention	180 18 17 16 15 14 13
in lines 1 and 2 above were	e in conformance with regulations ar structions of the United States Depar	tment of the Interior. Bureau of La	and 7
Management or by a decree (of a Court of Law and/or that the corne	er points mentioned in lines 3, 4 and	10 5 8 10 20 21 22 23 24
above were in conformance:	with the rules of the Michigan Board (of Land Surveyors or by a Decree o	ofa
Court of Law; established	, re-established, monumented, re-	monumented, recovered, found	as
expressed below:			10 30 29 28 27 26 25
NOTE: Not more than 4	corners, all in the same town a	nd range, may be recorded	11
on this certifical		-	12 32 33 34 35 36
y			13
A. Description of origina	al monument and accessories an	d/or subsequent restoration:	
	•		
	•		•
·		DC recorded in Liber 3 Page	201
See Remonument	ation Dossier for corner and LC	RC recorded in Liber 3, 1 ago	201
	•		
B. Description of corne	er evidence found and/or method	applied in restoring or reestat	blishing corner:
	aft in mon. box ±8 feet South of	centerline of M-55 per LCRC	recorded in Liber 3, Page 201.
Found 1" axie sha	iff in mon. box ±8 leet south of	Centerinic of 141-35 per 130-140	, ,
	•		
	•		
C. Description of monu	ment for corner and accessories	established to perpetuate loc	cating the position of the corner:
			TO THE STATE OF TH
Set Std. Roscon	nmon County mon. in mon. box	·	ROSCOMMUN COUNTY
			PEER GROUP APPROVAL
S 89° W - 101.72 - Set nail in Power Pole S 45° E - 41.98 - Set nail in Power Pole		ole	0 9 1991
			DATE 8-8-1996 Marm E. Myen MEM
	E - 49.45 - Set nail in Power Pole		Danson & OMMEN MOR
	V - 56.30 - Found nail in Power 1		- Line will
N28°V	i ibwo in iibii pimo - uc.oc - v	. 0.0	Marvin E. Myers, P.S.
. Sign	OF MICE		County Surveyor
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	C.		
16/	S. DEAN TO	Date	7-22-96
Signed by	GEERS		
Surveyor's Michael Lic	enser 8 31977		FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28. 1
121	No.		MERIZED MAY 14. 1
181	33977 / EA		•

LIRER 3 PAGE 306