BUHVEY &

MAY 28 1997 -

2392

COMMISSION CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Roscommon	Located In:	Corner Code #		STATE OF N		
(County)				ROSCOMKON Recor		
Public Land Survey	T 23N R 2W_	M - 9				
,. Tublic Edita Cartey	T R			18 APR 96 1	0:01 A.M.	
	T R			ROBERT W	. SHITH	
2. Property Controlling	T R S T R			REGISTER		
in Section	ST R		TO BE FILED	TN LIBER	3 OF LAND CORNER	
3. Miscellaneous	\$T R				o & File Number	
Property in Section	STR				J & The Number	
4. Lot No , F	Recorded Plat		A	B	:GHIJKLM	
			3			
			4 7	89	10-11-12	
Marvin E. Myers	, in a field survey on	March , 1996	, 5			
do hereby certify that under re	quirements of P.A. 74, Michigan P.A conformance with regulations and re	L of 1970, the corner points men	tioned 6	8-17-16	3-15-14-13-	
manual of survey instruction	is of the United States Departm	ent of the Interior, Bureau of	Land '			
Management or by a decree of	of a Court of Law and/or that the color with the rules of the Michigan 80	mer points mentioned in lines 3, and of Professional Surveyors o	raus III	9 20 21	22 23 24	
Decree of a Court of Law; esta	ablished, re-established, monument	ed, re-monumented, recovered,	found 9	0 29 27	3 - 27 - 26 - 25	
as expressed below:			11	29 2		
NOTE: Not more than 4 co	omers, all in the same town and	range, may be recorded	12 3	1 32 33	35-34-35-36-	
·			13			
•	monument and accessories and M. Schaaf		n: enning Feb. 9, 1	19/14		
GLO-William Burt 1852 Mon-Set Post	Mon-Fd. or	Mon-Fd	squared cedar	post with o	ld line	
WIT: 5" Tamarack SO4°W 4" Tamarack SO4°E			corner accepted cedar post 4"			
	2,00		-	•		
•						
B. Description of corner	evidence found and/or method	applied in restoring or rees	tablishing corner:			
Henning survey 1946	no evidence of cedar post	found. Reestablished pos	sition from ties	to corners	North and	
West as shown in Her M-9 to K-9 5175.80'						
M-9 to M-7 5763.69	the position of the origin	nal covernment corner				
A reestabilishment of	the posteron of the origin	dar government corner.	DOCCONE			
			ROSCOMMON COUNTY			
			PEER GROUP APPROVAL			
			DATE	PRICE 8	1996	
			Onywood	8. Muy	~ Whit	
Manual E Residence						
Marvin E. Myers, P.S. County Surveyor					> ,	
C Description of monum	nent for corner and accessories	established to pemetuate i			ner:	
Monument - Set 3/4" ID	x 54" pipe & cap "MEM 31600	O"		51 1115		
WIT: Set 4' wood stake Set 4' wood stake	3' into ground East 10.00' 3' into ground North 10.00	t	;		7	
Set 41 wood stake	3' into ground West 10.00' 3' into ground South 10.00		,		1	
Set carsonite post				× - 18.0		
				r		
			F**	+4 ↑ ?		
			`.			
\sim	(107.					
E MAN	ins Man	Date	April 11, 199		mel.	
Signed by						
Surveyor's Michigan Licer	nse No. 31600	FORM A	PPROVED BY MICHIGAN STATI	E BUARD OF PROFESSI	ONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975	