8371 SURVEY & REMONUMENTATION

ROSCOMMON COUNTY REMONUMENTATION

APR 2 4 1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF NICHIGAN ROSCOMMON COUNTY RECTRIFIED

Fo	or corners in COMN	MISSION		s serves etc.
_ <u>F</u>	Roscommon (County)	Located In:	Corner Code =##	15 NOV 94 9:13 A.M.
1.	Public Land Survey		I-13	ROBERT W. SMITH REGISTER OF DEEDS
2.	in Section	S T R S T R		TO BE FILED IN LIBER 3 OF LAND CORNERS
J.	Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number
		Recorded Plat		ABCDEFGHIJKLM
J .				2 6 5 4 3 2 1

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Brink set post 1837 Y. Pine 13 N61 E 21 1kg


34.

Y. Pine 13 N61½E 21 1ks Y. Pine 14 N72 W 12 1ks

1941 Henning set 3/4 " pipe Sec. Subdivision of Section

pe on 1956 Ostling Set concrete
Mon. for Plat of Trail's
end Annex L. 4 P. 5
Wit: 14" W. Oak N39°E 43.0'
18" B. Oak S17°E 51.6'

Corner of Sec. 2 & 3 T22NR3W. is 7.9 East of corner



Henning 1965 Plat of Northern Oaks L. 5 p. 49 Ostline 1966 Plat of Vienna Woods L. 5 P. 59

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.

November 1994 Arleth Found broken concrete monument at corner location.

Checked proper location from concrete monuments set in plats of Northern Oaks & Vienna Woods.

Found old wit: from 1956

Now 28" R. Oak S14°E (52.70 set N&T)

Found concrete monument corner of Section 2 & 3 T22N, R3W 7.9 East of

corner as recorded.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner. Set Roscommon County Standard Mon. in place of broken conc. mon. I-13

N & T 28" R. Oak S14°E 52.70

N & T 26" Twn. W. Oak S41°E 67.28'

N & T 10" Maple S84°W 54.17

N & T 20" W. Oak S45°W 30.64

Plat conc. mon. N89°54'E 147.0

Plat conc. mon. N89°54'E 233.3

Carsonite Post at corner.

NW cor. of Bldg. (conc. foundation) N87°E 54.75 SW cor. of Bldg. (conc. foundation) S58°E 44.35 Corner of Sec. 2 & 3 T22N, R3W concrete monument 7.9 East.

FRANK

ARLETH
SURVEYOR
NO.
21266

Signed by Michigan License No. 21266 P.S.

Peer Group Approved

ORM APPROVED BY MICHIGAN SHOWS BUILDE LAND SOVECOS, JAN. 28, 1971

LIBER 3 PAGE 151