

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Roscommon</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>23N</u> R <u>4W</u>	<u>B-9</u>
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Craig W. McVean, in a field survey on May 12 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

B-9 - GLO - Set 1/4" Post A. Curtis - 1852  
W. Pine 36" N18°W 51L.  
Y. Pine 28" S20°E 37L.  
- R. Ostling Survey & Report - 1954 - FND 1" Iron Pipe  
Set by Geo. Henning during road survey from original U.S. Survey BT.  
BT W. Oak 14" N34.25°W 67.0'  
BT R. Oak 20" N 53.5°E 67.0'  
- Co. Rd 300 Rd. Plan - Original U.S. Corner -  
1" Pipe - 36.8' S. of Plan CL. - G. Henning - 1959  
- LCRC L.1 P. 15 - L. Cavanagh - 1971  
FND 1 1/4" Pipe



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-9 - 1/4 Cor. Common to Sec. 19 & 30, T23N, R4W - FND 1" x 23" I.D. Iron Pipe - Down 14" - 37' S of Phy CL. Co. Rd. 300 in CL. of Rd. to South. Monument agrees with Ostling Survey dimension's E & W and LCRC Description.

Monument accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-9 - Replace 1" x 23" Iron Pipe with 2 3/4" x 21" Roscommon Co. Mon. in Mon. Box.  
N50°W 126.15' to N&T in NE Side 16" R. Pine scribed 'XBT'  
N5°E 83.14' to N&T in E. Side 4" R. Pine Scribed 'XBT'  
N30°E 100.13' to N&T in SE Side 4" W. Pine Scribed 'XBT'  
S45°E 42.59' to N&T in SW Side UP  
N89°W 42' to Orange Carsonite Post

Signed by Craig W. McVean  
Surveyor's Michigan License No. 39088

Date 7/11/97