

925218 1894

STATE OF MICHIGAN
COUNTY OF ROSCOMMON

ROSCOMMON COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Dec 28 10 47 AM '93

COMMISSION

For corners in

Roscommon

(County)

Located in:

Corner Code #

- | | | |
|------------------------------------|------------|-------|
| 1. Public Land Survey | T 23 R 1 W | I - 8 |
| | T R | |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

ROSCOMMON COUNTY
PEER GROUP APPROVAL
DATE 12-14-93

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Frank J. Arleth, in a field survey on December, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

William Burt Set post 1852
S. Pine 8" S43°W 20 Lks.
S. Pine 7" N17°E 12 Lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

West ¼ corner of Section 23, T23N, R1W., found axle shaft in mon. box in centerline of highway M-76. corner set by Henning in 1947 when He made a section subdivision of said section. All witness destroyed.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Roscommon County Std. Mon. Stamped I - 8

Nail & tag 8" J. Pine N57°W 51.45
Nail & tag in power pole N87°E 73.35
Nail & tag in power pole S18°E 132.68
Northeast corner of log house foundation S45°W 135.20 feet
½" bar East 50.0



Signed by

Frank J. Arleth

Date

22 DEC 93

Surveyor's Michigan License No.

21266

Date December 14, 1993

Peer Group Approved

LIBER

3 PAGE

78