


LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich P.A. 1970

For corners in
 Roscommon County

Located in: Corner Code #

1. Public Land Survey

T24N R1W L-1
 T R
 T R
 T R



I, Larry L. Cavanagh, in a field survey May 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in line 1 above was in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

FILE IN LIBER 3 OF LAND CORNERS
 Register of Deeds Stamp & File Number

A. Description of original monument and accessories and/or subsequent restoration:

JOHN BRINK 1839	NORM PARKER, RLS MAY 1975
SET POST	LCRC L2, P16
W. PINE 28° N70°E 26 LKS	FD NAT'L FOREST MON
Y. PINE 18° N51°W 70 LKS	6° W. OAK N85°W 9.35'
	8° OAK NORTH 3.41'
T.N. CANADA 1937	
FD REMAINS OF ORIGINAL BEARING TREES	NORM PARKER, RLS MAY 1975
SET CONC MON 6' DIA X 24' / BRASS CAP & STEM	L145, P287
LOCAL BEARING TREES	FD NAT'L FOREST MON
6° W. OAK N32 1/4°E 57 LKS (NET)	NO WITNESSES
6° W. OAK N29 3/4°W 80 LKS (NET)	
NEW BEARING TREES	
7° W. OAK N27 1/2°E 48 LKS	
9° N PINE N73 1/2°W 71 LKS	

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND GLO MONUMENT/ FOREST SERVICE GUARD POST & TAG
 FOUND PARKER WITNESSES FROM 1975
 FOUND 10° W. OAK N25°E 31.6' TO CENTER OF TREE (POSSIBLE 1937 WITNESS)
 FOUND 18° N. PINE N75°W 46.5' TO FACE (POSSIBLE 1937 WITNESS)

A PERPETUATION OF THE ORIGINAL GOVERNMENT CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

LEFT US-GLO MONUMENT IN PLACE 9' NORTH OF CENTERLINE OF TRAIL
 WIT: NAIL & TAG IN 7° W. OAK N306°W 52.44'
 NAIL & TAG IN 8° R OAK N7°E 3.35'
 NAIL & TAG IN 7° W. PINE S34°W 37.24'
 NAIL & TAG IN 7° W. PINE S43°E 41.70'
 CARSONITE POST SOUTH 18.4'

RUSCOMMON COUNTY
PEER GROUP APPROVAL

DATE Sept 10, 1999
Marvin E. Myers
 Marvin E. Myers, P.S.
 County Surveyor

CRAWFORD COUNTY
PEER GROUP APPROVAL

DATE Sept 10, 1999
Marvin E. Myers
 Marvin E. Myers, P.S.
 County Surveyor



Signed by Larry L. Cavanagh
 Surveyor's Michigan License NO. 17614

Date Sept. 14, 1999

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN., 1983



LIBER 3

PAGE 624

SURVEY &
 RECONSTRUCTION

MAR 1 2000

SECTION