

SURVEY & REMONUMENTATION

8363

APR 24 1995

ROSCOMMON COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

COMMISSION

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
ROSCOMMON COUNTY
RECORDED

For corners in

Roscommon
(County)

Located In:

Corner Code #

15 NOV 94 9:06 A.M.

ROBERT W. SMITH
REGISTER OF DEEDS

1. Public Land Survey T 24 R 2 W C-6
2. Property Controlling S T R
3. Miscellaneous S T R
- Property in Sec. S T R

TO BE FILED IN LIBER 3 OF LAND CORNERS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Frank J. Arleth, in a field survey on November, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Set post Brink 1837 - Burt 1852
S. Pine 10" N77°30'W 3.05
S. pine 8" N75°E 4.19

Delamater in 1929 set 1" pipe
6" spruce S45°E 22.2

1953 Henning found 1" pipe
set by delemater.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Arleth October 1994 found 1" x 5' pipe in corner.
area clear cut to East and B.T. destroyed.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Roscommon County standard monument
N & T 12" J. pine N23°30'E 45.75
N & T 12" J. pine N48°E 48.84
N & T 30" triple oak S71°E 39.25
N & T 10" J. pine S40°E 62.53
N & T 16" J. pine S14°30'E 69.48
Carsonite post East 13.85

C-6

Corner in centerline of trail West.



Signed by Frank J. Arleth Date 11/10/94
Surveyor's Michigan License No. 21266 P. S.

DATE 10/20/94 Peer Group Approved

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

LIBER 3 Page 143