

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Roscommon

(County)

Located In:

Corner Code #

STATE OF MICHIGAN
 ROSCOMMON COUNTY
 RECORDED

9 JUN 99 3:51 P.M.

ROBERT W. SMITH
 REGISTER OF DEEDS

1. Public Land Survey

T 24N R 4W

D-1

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

FILE IN LIBER 3 OF LAND CORNERS
 Register of Deeds Stamp & File Number

I, Marvin E. Myers, in a field survey on April, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. - 1839 John Brink, D.S.

Mon - Post

Wit: 7" Pitch Pine N64°E 26 lks.

7" Pitch Pine N46°W 34 lks.

Marcus Schaaf 1940's

Mon - Iron Set

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Schaaf 1 1/2" pipe in concrete. Accepted pipe as the best available evidence of the position of the Original Corner. Replaced pipe with Standard Crawford County Monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon: Standard Crawford County Monument.

Wit: West edge of Carsonite Post N51°E 33.78

Nail in E. side 3" J. Pine S30°E 69.21

Nail in NE side 3" J. Pine N54°W 41.59

Nail in NW side 5" J. Pine N37°E 44.48

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	5	5		4	3					2		1	
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

ROSCOMMON COUNTY
PEER GROUP APPROVAL

DATE April 19, 1999

Marvin E. Myers
 Marvin E. Myers, P.S.

County Surveyor

SURVEY &
 RE-ESTABLISHMENT

MAR 11 2000

SECTION

Signed by

Surveyor's Michigan License No. 31600Date June 2, 1999

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN., 1983
 REVISED OCT., 1995

LIBER 3 PAGE 603