

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Roscommon
(County)

Located In

Corner Code #

1. Public Land Survey T 24N R 4W H-4
T
2. Property Controlling in Section S 10 T 24N R 4W 11
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on September 23, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

H-4 Liber 1, Page 181, 1979 Kenneth J. Ostling
P.S. #10068 Set a 5/8 iron rod with P.S. cap at the
intersection of true 1/4 lines.

Wit: 14" Red Oak N70°W 40.30'
12" W. Oak S30°W 15.95'

11- George D. Henning L.S. # 2240 1983, set 1/2" x 18" steel
bar.

Wit: 8" J. Pine S65°E 21.7'
4" W. Pine N20°E 4.83'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-4 Found 5/8" iron rod with P.S. cap # 10068.

11- Found 1/2" iron rod added P.S. cap #33981.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-4 5/8" iron rod with P.S. cap # 10068.

Wit: 16" Oak S30°W 16.61'
14" Oak N67°W 40.62'
7" Oak S77°E 28.63'
10" Oak N24°W 27.61'
Blue Carsonite Post North 1±

11- 1/2" iron with P.S. cap # 33981

Wit: 12" W. Pine S89°W 17.56'
8" W. Pine N32°E 4.87'
1" Pipe N25°E 4.87'
6" Oak S03°W 19.48'
Blue Carsonite Post North 1±

Signed by:

Carl T. Kiiskila

Date:

10-8-03

Surveyor's Michigan License No.:

33981

