

JAN 22 2001

LIBER

3 PAGE 31

RECEIVED FOR RECORD

00 NOV 27 AM 8:55

SECTION

2000 Remonumentation Program  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER NO. 3 PAGE NO. 31  
MICHELE VANNORMAN  
REGISTER OF DEEDS  
SANILAC CO., MICHIGAN

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T11N R15E

I - 7

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

2000

I, John A Milletics in a field survey on May 1, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	19	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO Notes

Birch 15" 84½W 24 Links

Hemlock 18" S57°E 16 Links

Act 132 - Liber 3 Page 741 - Sanilac Land Surveying 1977

L.C.R.C Forms - None

Unrecorded surveys - Sanilac Land Surveying 1981, Milletics 1998

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I - 7

SW Corner Section 14 T11N-R15E

Found 5/8" Iron Bar in gravel road bed

West 2650.80 feet to the S 1/4 Corner Section 15

East 2653.96 feet to the S 1/4 Corner Section 14

Accepted as best evidence

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I - 7

SW Corner Section 14 T11N-R15E

5/8" Iron Bar in gravel road bed

N40°E 30.42 feet to a nail in a mail box post

N45°E 76.35 feet to a nail in a Power Pole

N45°E 46.60 feet to a 1/2" Iron Bar

N70°E 55.00 feet to a stop sign

S45°W 39.10 feet to a stop sign

S40°E 47.20 feet to a Michigan Bell Cable Box

West 2650.80 feet to the S 1/4 Cor Sec. 15 - East 2653.96 feet to the S 1/4 Cor Sec. 14

APPROVED PEER BOARD  
MEETING NOV 25 2000

91

Signed by John A Milletics

Date Nov 15, 2000

Surveyor's Michigan License No. 25859