

JAN 22 2001

LIBER

3 PAGE 32

RECEIVED FOR RECORD

SECTION

2000 Remonumentation Program
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

00 NOV 27 AM 8:55

LIBER NO. 3 PAGE NO. 32
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac Located In: Corner Code #
(County)

1. Public Land Survey T11N R15E L-1
T R
T R
T R

2. Property Controlling S T R
In Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

i. Lot No. _____, Recorded Plat _____
j. Private Claims _____

2000
John A. Millerics in a field survey on May 1, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Description of original monument and accessories and/or subsequent restoration:

GLO Notes
None

Old Survey Liber - None
Act 132 - None

L.C.R.C Forms - none
Unrecorded surveys Found none


Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L - 1
N 1/4 Corner Section 1 T11N-R15E
Found no evidence of corner on site - State Highway has just removed pavement for construction
West 2648.41 feet to the NW Corner Section 1
East 2638.00 feet to the NE Corner Section 1
Accepted as best evidence

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L - 1
N 1/4 Corner Section 1
1/2" Iron Bar in pavement with cap
West 6.27 feet to the S 1/4 Corner Section 36
North 6.0 feet to the Centerline of M - 46
South 54.15 feet to a R/W Marker
N50°E 154.50 feet to a nail in a Power Pole
N45°W 155.35 feet to a nail in a Power Pole
West 2648.41 feet to the NW Corner Section 1
East 2638.00 feet to the NE Corner Section 1

APPROVED PEER BOARD
MEETING NOV 25 2000



Drawn by John A. Millerics
Surveyor's Michigan License No. 25859

Date Nov 15, 2000