## JAN 2 2 2001

SECTION

3 PAGE 56 LIBER

RECEIVED FOR RECORD

00 NOV 29 AH 11: 11

	LAND CORNER RECORDATION CERTIFICATE
For corners in	Filing Requirement of Act 74, Mich. P.A. 1970
	0.000

2000 REMONUMENTATION PROGRAM

Sanilac Located In: Corner Code #

 Public Land Survey T11N R16E

2. Property Controlling in Section 3. Miscellaneous Property in Sec.

LIBER NO. 3 PAGE NO. MICHELE VANNORMAN REGISTER OF DEEDS SANILAG CO. MICHIGAN

Register of Deeds Stamp & File Number

\_, Recorded Plat\_ . Private Claims

2000

John A Milletics, in a field survey on May 1 ZEK. do hereby state that under equirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in onformance with regulations and rules therefore as required in the current manual of survey instructions of the nited States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or at the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan pard of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, covered, found as expressed below:

OTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration: GLO Notes

Hemlock 30" S65°E 38 Links Sugar Maple 24" N63°W 26 Linke

Act 132 - Liber 1 Page 162 Chope Oct 1971

L.C.R.C. Forms - None Old Survey Liber - None Unrecorded surveys - None

State Highway Book Page 73

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

. Lot No.

NE Corner Section 6 TllN-R16E

Found no evidence of corner at site - State Highway Department removed

corner during construction

West 2658.28 feet to the N 1/4 Corner Section 6

2611.30 feet to the N 1/4 Corner Section 5

Accpeted as best evidence

APPROVED PEER BOARD MEETING Nov 25, 2000

William W.

Actionste

1 - 212 5

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NE Corner Section 6 Tl1N-R16E

1/2" Iron Bar with cap in concrete

East 10.18 feet to the SE Cor Sec. 31

South 3.5 feet to the Centerline of M - 46

S40°E 62.22 feet to a nail in a Light Pole

S45°W 62.40 feet to a nail in the top of a cut off Telephone Pole

N40°E 67.45 feet to a Right of Way Marker

N40°W 58.42 feet to a cable marker post

West 2658.28 feet to the N 1/4 Corner Section 6

East 2611.30 feet to the N<sub>1</sub>/4 Corner Section 5 and by

ned by \_ veyor's Michigan License No. 25859

Nov 15, 2000 Date

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975