

JAN 22 2001

LIBER 3 PAGE 72

RECEIVED FOR RECORD

SECTION

2000 REMONUMENTATION PROGRAM  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

00 DEC -1 AM 9:33

LIBER NO. 3 PAGE NO. 72  
MICHELE VANNORMAN  
REGISTER OF DEEDS  
SANILAC CO., MICHIGAN

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T11N R 16E

H - 7

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

2000

I, John A Milletics, in a field survey on May 1, 19x do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H - 7

S 1/4 Corner Section 15 T11N-R16E

GLO Notes

Beech 16" N32°E 27 Links

White Ash 10" S19°E 15 Links

Act 132 - None

UNrecorded surveys - Milletics Oct 1982

L.C.R.C. Forms - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H - 7

S 1/4 Corner Section 15 T11N-R16E

Found 1/2" Iron Bar in gravel road bed

West 2654.10 feet to the SW Corner Section 15

East 2654.10 feet to the SE Corner Section 15

Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H - 7

S 1/4 Corner Section 15 T11N-R16E

1/2" Iron bar in gravel road bed

N70°W 68.15 feet to a nail in a 18" Ash tree

N05°E 31.20 feet to a nail in a wooden fence post

N40°E 54.20 feet to a nail in a 24" apple tree

S02°W 61.30 feet to a nail in a Power Pole

West 2654.10 feet to the SW Corner Section 15

East 2654.10 feet to the SE Corner Section 15

APPROVED PEER BOARD  
MEETING NOV 25 2000

Signed by John A. Milletics  
Surveyor's Michigan License No. 25859

Date Nov 15, 2000

