

JAN 22 2001

LIBER

3 PAGE 46

RECEIVED FOR RECORD

00 NOV 27 AM 8:56

SECTION

2000 Remonumentation Program
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Sanilac
(County)

Located In:

Corner Code #

LIBER NO. 3 PAGE NO. 46
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

1. Public Land Survey

T12N R16E		F - 7
T	R	
T	R	
T	R	
T	R	
S	T	R
S	T	R
S	T	R
S	T	R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

Lot No. _____, Recorded Plat _____
Private Claims _____

Register of Deeds Stamp & File Number

John A Milletics, in a field survey on May 1, 2000
requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in
formance with regulations and rules therefore as required in the current manual of survey instructions of the
nited States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or
at the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan
ard of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,
covered, found as expressed below:

OTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Description of original monument and accessories and/or subsequent restoration:

GLO Notes

Pine 28" S9°E 19 Links

Pine 12" N81½°W 19 Links

Act 132 - Liber 4 Page 304

Road Comm- None


L.C.R.C. - None

Unrecorded surveys - Milletics July 1994,

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F - 7

S 1/4 Corner Section 16 T12N-R16E
Found 1/2" Iron Bar in gravel road bed
West 2600.18 feet to the SW Corner
East 2611.08 feet to the SE Corner
Accepted as best evidence



Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F - 7

S 1/4 Corner Section 16 T12N-R16E
1/2" Iron Bar in gravel road bed
S45°E 55.00 feet to a nail in a 12" Poplar
S20°W 45.42 feet to a nail in a 12" Poplar
North 33.00 feet to a 1/2" Iron Bar
N15°E 40.80 feet to a nail in a 18" Birch
West 2600.18 feet to the SW Corner
East 2611.08 feet to the SE Corner

APPROVED PEER BOARD
MEETING NOV 25 2000

ed by John A. Milletics
eyor's Michigan License No. 25859

Date Nov 16, 2000