

RECEIVED FOR RECORD

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

98 DEC -1 AM 9:08

LIBER NO. 2 PAGE NO. 235

For corners in

Sanilac

(County)

Located In:

Corner Code #

1. Public Land Survey

T13N R13E A-2

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, John A. Milletics, in a field survey on Oct 5, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-2 GLO Notes - Elm 12 N21 1/2W 11; Birch 6 S9W 40
Old Survey Liber - None
Act 132 Liber 4 Page 122
Road Comm. - None
L.C.R.C. - None

SURVEY &
REMONUMENTATION

JAN 15 1999

SECTION

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-2 Found 1/2" Iron Bar as recorded in Liber 4, Page 122
accepted as best evidence

South 2652.51' to SW Corner Section 6

North 2735.72' to NW Corner Section 6

APPROVED PEER BOARD MEETING
NOV 30, 1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-2

1/2" Iron Bar with cap

North 25.20 feet to a nail in a Wooden Fence Post

North 2.00 feet to a nail in a Wooden Fence Post

N45°E 35.60 feet to a nail in a Wooden Fence Post

East 31.50 feet to a nail in a Wooden Fence Post

S50°E 39.55 feet to a nail in a 10" Apple Tree

South 2652.51' to SW Corner Section 6
North 2735.72' to NW Corner Section 6

Signed by



Date

Nov 18, 1998

Surveyor's Michigan License No. 25859