

ST. CLAIR COUNTY, MICHIGAN



AND SER	OFFICIAL GOVERNMENT C	ORNER
SURVEYOR NO. 24608 LAND SURVEYOR LAND SURVEY	LAND CORNER RECORDATION CER	
A Some Wall	Filing Requirement of Act 74, Mich.	
NO LAND 3	Located In: Corner Code ≠#	REG ST
	CILY OF SC. CIAIL	
1. Public Land Survey	TOSV R16E #2	<u>5</u> ₩ 30
	T R T R	70 - 4UV
	T R	
2. Property Controlling	S T R	
in Section	S T R	OC 4
3. Miscellaneous	STR	Register of Deeds Stamp & File Number
Property in Sec.	S T R ·	
4 Lat No De	and the Plat	1
4. LOLINO A9	Corded Plat	
5. Private Claims 306	corded Plat	A B C O E F G H ! J K L)
5. Private Claims	Intersection west line P.C. 306 with south	A B C O E F G H ! J K L I
5. Private Claims	Intersection west line P.C. 306 with south	A B C O E F G H ; J K L I
5. Private Claims 306 T5N-R	Intersection west line P.C. 306 with south 16E and north line of T4N-R16E. 001	A B C D E F G H ; J K L A
5. Private Claims 306 T5N-R. John C. Niederhauser	Intersection west line P.C. 306 with south 16E and north line of T4N-R16E. 001 in a field survey on	96
5. Private Claims 306 T5N-R: John C. Niederhauser do hereby certify that under requ	in a field survey on	96 STOPE STOP STOPE STOP
5. Private Claims	in a field survey on	96 13 17 16 15 14 13
John C. Niederhauser do hereby certify that under require lines 1 and 2 above were in current manual of survey instructions and agement or by a decree of a Comment of the survey in the	in a field survey on	1 line 2 6 5 4 3 2 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
John C. Niederhauser do hereby certify that under require lines 1 and 2 above were in current manual of survey instructions above were in conformance with	in a field survey on	1 line 2 6 5 4 3 2 1 2 3 3 4 7 8 9 10 11 12 12 13 15 14 13 15 15 14 13 15 15 14 13 15 15 16 15 16 15 16 16 16 16 16 16 16 16 16 16 16 16 16
John C. Niederhauser do hereby certify that under require lines 1 and 2 above were in current manual of survey instruct Management or by a decree of a cabove were in conformance with Court of Law; established, re-	in a field survey on	1 line 2 6 5 4 3 2 3 3 2 3 3 4 7 8 9 10 11 12 12 13 15 15 14 13 15 15 14 13 15 15 14 13 15 15 14 13 15 15 16 16 16 16 16 16 16 16 16 16 16 16 16
John C. Niederhauser do hereby certify that under require lines 1 and 2 above were in current manual of survey instructions above were in conformance with	in a field survey on	96 ntioned in the of Land 4 and 5 ree of a und as 10 30 29 28 27 26 3 3 2 3 3 2 3 3 3 3
John C. Niederhauser do hereby certify that under require lines 1 and 2 above were in current manual of survey instruct Management or by a decree of a Cabove were in conformance with Court of Law; established, reexpressed below:	in a field survey on	1 line 2 6 5 4 3 2 3 3 2 3 3 4 7 8 9 10 11 12 12 13 15 15 14 13 15 15 14 13 15 15 14 13 15 15 14 13 15 15 16 16 16 16 16 16 16 16 16 16 16 16 16

A. Description of original monument and accessories and/or subsequent restoration:

William Preston set a wood post in 1817 as the original government corner of Fractional Section 2 (T4N-R16E) and Fractional Section 35 (T5N-R16E) at the intersection with the west line of Private Claim No. 306. This corner is common to two (2) townships and a Private Claim. Nothing listed for corner on Old County Surveyors Record. John Lansky P.S. found and used a 4 " iron rod, see survey Liber 1, page 55. L.C.R.C. recorded by John Lansky P.S., see Liber 1, pages 69 and 70. Corner listed on survey by John Lansky P.S., see survey Liber 3, page 29. Gerald James found a capped iron #5557 and confirmed from witnesses, see Liber 12, pages 227 and 228. Corner listed on TRV survey dated July 7, 1995.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found a 14" iron rod with cap # 5557, 67 feet south of the centerline of Fred Moore Highway, in line with a tree row south-southwest. Verified corner from found witnesses and listed distances on recorded surveys. **SURVEY &**

REMONUMENTATION

JUL 1 4 1997

COMMISSION

Ο.	Description of monument for corner and accessories established to	per c	rpetuate	locating	the	position	of the	e corni	er:
----	---	-------	----------	----------	-----	----------	--------	---------	-----

Set a 2" diameter aluminum cap with a magnet attached and inscribed "St. Clair County Official Corner" on the existing 4" iron rod. This corner marks the intersection of the south line of T5N-R16E, the north line of T4N-R16E and the west line of Private Claim No. 306.

N 24°W 135.14 feet to a set P.K. nail with county remon. tag in east side of power pole.

N 19°E 125.23 feet to a set P.K. nail with county remon. tag in east side of power pole. N 67°E 95.77 feet to a set P.K. nail with county remon. tag in west end of concrete curb.

S 58°W 25.55 feet to a set P.K. nail with county remon. tag in east side 24" poplar tree.

NORTH 67.2 feet to the centerline of pavement of Fred Moore Highway.

WEST 2289.32' to a found iron #19835 at the north 4 corner of Section 2, T4N-R16E.

EAST 487.75' to a found P.K. nail at the centerline of King Road.

PA 345-1990 PEER COMMITTEE

	<u> </u>		Wanter
Signed by	of Africanos	Date	July 29, 1

Surveyor's Michigan Licedse No.

LIBER 008 PAGE 268