

ST. CLAIR COUNTY, MICHIGAN
OFFICIAL GOVERNMENT CORNER



LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Located In:

Corner Code ##

1. Public Land Survey

T 6N R 15E

B-1

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous

S _____ T _____ R _____

Property in Sec.

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	16	17	18	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

David J. Little in a field survey on Sept. 27-30, 1993

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 1 corner, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This Corner not set on Government Surveys

**Nothing listed on Old Surveyor's Record
St. Clair County.**

Nothing recorded for this Corner.

STATE PLAIN COORDINATES

N. _____

E. _____

ELEVATION _____

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set "T" Iron stamped LLS 31596.

Set "T" Iron on line with the NW Corner Section 6, T6N, R15E and the NE Corner Section 6, T6N, R15E, and also in line with Old fence line running South.

**Corner is 5.0' North of fence running East for about 60' only.
Corner is in agreement with fence going South.**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set "T" Iron stamped LLS 31596.

2159A000 12/29/93MSU4 9.00

0001

SE 21.0' to set P.K. and County Tag in W face of 24" Beech.

E. 58.60' to set P.K. and County Tag in N face of 60" Maple.

N. 28.17' to set P.K. and County Tag in E face of 15" Beech.

WNW 27.30' to set P.K. and county Tag in N face of 18" Maple.

See attached sketch for additional information.

2159A000 12/29/93SSRF4 2.00

0001

Signed by

David J. Little

Date

December 18, 1993

Surveyor's Michigan License No.

31596

PA 345-1990

PEER COMMITTEE

APPROVED 12-14-93

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

Signed By:

St. Clair County Land Surveyor

Date

Surveyor's Michigan License No.

LIBER 007 PAGE 183