

RECEIVED
ST. CLAIR COUNTY

1994 SEP 20 PM 2:24

REGISTER OF DEEDS
ST. CLAIR COUNTY

ST. CLAIR COUNTY, MICHIGAN
OFFICIAL GOVERNMENT CORNER



LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Located In:

Corner Code #

1. Public Land Survey T 7N R 15E I-13
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, David J. Little, in a field survey on October 4, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 1 corner, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
Post-(Government Surveys)

Stone and P.K. are shown on Old Surveyor's Record
St. Clair County.

P.K. Recorded in L.2 P.254 of Recordation Certificates
Note: This P.K. does not agree with this corner.

STATE PLAIN COORDINATES

N. _____

ELEVATION _____

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Set Painted "X" in conc. pavement.

Corner was set on line with the NE Corner Section 3, T6N, R15E and the S. $\frac{1}{4}$ C
Section 34, T7N, R15E and using the P.K. and the E. $\frac{1}{4}$ Corner to establish the
East line Section 34, T7N, R15E.

The 1952 Michigan State Highway Department Plans do not reference this Corner

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set Painted "X" in conc. pavement.

NW 68.90' to set P.K. and County Tag in E. face of D.E.P.
NE 58.20" to set P.K. and County Tag in W. face of Utility Pole
SW 64.22' to set P.K. and County Tag in N. face of D.E.P.

See attached sketch for additional information.



Signed by David J. Little
David J. Little

PA 345-1990
PEER COMMITTEE
APPROVED 6-24-94

Date November 20, 1993

Surveyor's Michigan License No. 31596

APPROVED AS AN OFFICIAL GOVERNMENT CORNER BY ST. CLAIR COUNTY:

Signed By: _____
St. Clair County Land Surveyor

Surveyor's Michigan License No. _____

LIBER 007 PAGE 391

Z



Age: ALL DIST.
WEAS: O.M.E

DAVID J. LITTLE
2833 GRATIOT BOULEVARD, MARYSVILLE, MICHIGAN 48040
LICENSED LAND SURVEYORS

