For corners in

NOV 6 - 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
| LIBER 5 PAGE 37

Corner Code # (County) LEONIDAS TWP.	STATE OF MICHIGAN ST. JOSEPH COUNTY
1. Public Land Survey T	FILED 31 OCT 97 11:34 A.M.
2. Property Controlling S T R	CYNTHIA JARRATT REGISTER OF DEEDS
Property in Sec. S TR	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat 5. Private Claims	A B C D E F G H I J K L M 2 6 5 4 3 2 1
NAYNE A. MOSTROM, in a field survey on 2015 97 do hereby state that und requirements of P.A. 74, Michigan P.A. of 1970, the comer points mentioned in lines 1 and 2 above were conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumenter recovered, found as expressed below:	in he 5
NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate.	9 10 30 29 28 27 26 25 11 11 12 31 32 33 34 34 35 36 1
A. Description of original monument and accessories and/or subsequent restoration:	13
1865 SURVEY IN A/99 1944 RAILROAD SURVEY	LCRC IN 3/196 (1991)
NO IDENTIFY-SHOWN AS "T-RAIL" 4 1/2' HIGH 39.96 CH. SOUTH OF NW COR	FD. RR RAIL POST 4.6' HIGH TWIN 10" MULB = N30°W 34.85' TWIN 14" MULB = NORTH 47.4'
1883 SURVEY IN A/448 STONE SET BY FORMER SURVEYOR FROM BRG. STUMP	6.4' N OF E-W FENCELINE 82'± SOUTH OF RIVER
B. Description of corner evidence found and/or method applied in restoring or reestablishing	corner:
FOUND RR RAIL IN CONC. BASE 4.6' HIGH BOTH MULBEERY TREES ARE OK FROM 1991 LCRC EAST-WEST FENCE HAS BEEN REMOVED CORNER IS 82'± SOUTH OF RIVER	RATIFIED BY PEER GROUP IN ACCORDANCE WITH P.A. 345 ON Sept. 8; 1997 CO. REPRESENTATIVE
	and in the second of the secon
C. Description of monument for corner and accessories established to perpetuate locating the	position of the corner:
CHISELED "+" ON TOP OF RR RAIL IN CONC. 4.6' HIGH NEW IN E SIDE 12" DBL ELM = NORTH 14.23' NEW IN S SDIE RR TIE POST = S40°E 14.31' NEW IN NW SIDE 8" LOCUST = S20°W 76.76' NEW IN S SIDE 8" LOCUST = S50°W 69.10' COR. IS AT APPROX HIGH BANK OF RIVER	WAYNE A. MOSTROM PROFESSIONAL SURVEYOR NO 14100 PROFESSIONAL PROFESSIONAL NO 14100 PROFESSIONAL PROFESSION
Signed by Court Date	OCTOBER 31, 1997
Surveyor's Michigan License No. 14100	