

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Mendon Twp.

St. Joseph Located In: Corner Code #
(County)

1. Public Land Survey T 5S R 10W H-5
T R
T R
T R
T R

2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

LIBER 6 PAGE 2
STATE OF MICHIGAN
ST. JOSEPH COUNTY
FILED

7 JAN 2000 9:45:29 AM

CYNTHIA L. JARRATT
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, David W. Mostrom, in a field survey on 9/10, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(H-5) 1/4 Corner common to Sections 10 & 15 T5S, R10W
NW cor. of Nottawasepe Indian Reserve

- * GLO Post
8" W. Oak = N05°E 21.12'
16" W. Oak = S14°W 37.62'
- * 1876 Survey in Bk A, Pg 238
+ 'd stone in shape of a boot
set from old bearings
6" Basswood = N22°E 64.68'
- * 1896 Survey in Bk A, Pg 737

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fd. 3/4" x 36" pipe in Mon. box in cut area
of roadway - dug 42" below road surface & fd.
no evidence of stone
All witnesses check to 1998 Survey
Set 5/8" x 24" iron bar w/std. cap in place of pipe
in Mon. box

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON Sept. 13, 1999
Albion CO. REPRESENTATIVE

+ 'd stone set by Andrews
Basswood = N22°E 64.68'
8" B. Oak = N66°W 35.53'

* 1968 Sayers Survey
Cor. not labeled or witnessed

* 1974 LCRC in Bk 1, Pg 99
Pipe in box found
Guard post = SE 47.4'
P. Pole = NE 62.4'
C Road = South 3.5'

* 1998 Mostrom Survey
Fd. 3/4" pipe in Mon. box
10" Poplar = S60°W 65.53'
8" Maple = S20°W 140.75'
Top of C.M.P. = S40°E 47.20'
Cor. is in C of E-W road
& 7.5' West of N-S road

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5/8" x 24" iron bar w/std. cap in Mon. box
N & W 1.0' high on E. side of P. Pole = N45°E 64.84'
E. side stop sign 1.0' high = S33°E 49.92'
N & W 2.0' high in W. side of 12" Maple = S59°W 65.34'
5/8" bar = N32°W 38.92'

Signed by David W. Mostrom
Surveyor's Michigan License No. 32339

Date September 21, 1999



LIBER 6 PAGE 2