

SURVEY & REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

004 PG 026

For corners in

ST. JOSEPH APR 10 1995

Located In:

Corner Code 77

FLOWERFIELD Twp

1. Public Land Survey

T 55 R 12W

K-11

2. Property Controlling in Section

S T R

3. Miscellaneous Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

FILED

APR 28 1 09 PM '94

Cynthia A. Lamm

REGISTER OF DEEDS
Register of Deeds Stamp & File Number

I, WAYNE A. MOSTROM, in a field survey on APRIL 11, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO

1967 BY ROAD COMMISSION

20" W.O. = S58°W 2.90
18" BLK.O. = N47°E 4.20

POINTED STONE IN MON. BOX
44" BLK. CHERRY = N30°W 49.62'
16" CHERRY = N82°W 25.47'
15" CHERRY = S70°E 36.79'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FD. 3/4" BAR OVER STONE (3.6' DEEP) IN MON. BOX
FD. REMAINS OF CHERRY STUMP S70°E 36.79'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

CORNER COMMON TO SECTIONS 25, 26, 35, 36

SET 5/8"X24" BAR WITH STANDARD CAP OVER STONE IN MON. BOX
CORNER IS IN TREE LINE TO E & EDGE WOODS TO W & 1.5' E OF C/L PAVEMENT
N & W 24" HIGH IN NE SIDE 38" OAK = N80°W 58.12'
N & W 24" HIGH IN NE SIDE 12" OAK = N30°W 68.88'
N & W 24" HIGH IN NE SIDE 12" OAK = N20°W 84.22'
N & W 24" HIGH IN W. SIDE P. POLE = S20°E 125.60'

APPROVED BY PEER GROUP
4/11/94 AS "BEST
AVAILABLE EVIDENCE
OF CORNER"



Signed by

Wayne A. Mostrom

Surveyor's Michigan License No. 14100

Date APRIL 12, 1994-28-74

REMONUMENTATION