

JAN 24 1996

004 PG 020

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ST. JOSEPH  
(County)

Located In:

Corner Code: #

FILED

COLON TWP.

1. Public Land Survey

T 6S R 9W

D-3

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

DEC 7 10 48 AM '93

Cynthia R. Lammert  
REGISTER OF DEEDS  
ST. JOSEPH CO MICH

Register of Deeds Stamp & File Number

I, WAYNE A. MOSTROM, in a field survey on OCT. 11, 19 93,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO

ROAD COMMISSION - 1965

9" W.O. = S52 1/3°E 56 LKS  
12" W.O. = N37 1/2°E 36 LKS

1/2" PIPE OVER +D STO. IN MON. BOX  
RR RAIL A.P. = N45°W 40.63'  
16" HICK = S15°E 56'  
CONC A.P. = S53°W 52.45'  
REMAINS OF W.O. STUMP 1/2 S65°W 67.03'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND +D STO. IN MON. BOX  
RR RAIL A.P. = N45°W 40.63'  
CONC. A.P. = S53°W 52.45'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SOUTH 1/4 COR. SEC. 5

SET 5/8" X 10" BAR OVER +D STONE IN MON. BOX  
COR IS IN CL E-W RDWY, 1' E OF CL TO N & 4.5' E OF CL TO S.  
RR RAIL A.P. = N45°W 40.63'  
FACE OF CONC POST = S53°W 52.45'  
FACE OF CONC POST = S30°W 55.2'  
N & W IN SE SIDE P.P. = N60°E 96.23'

APPROVED BY PEER GROUP  
AS REESTABLISHMENT OF  
ORIGINAL CORNER

Signed by Wayne A. Mostrom  
Surveyor's Michigan License No. 14100

Date OCT. 12, 1993

