

# SURVEY & REMONUMENTATION

NOV 15 1994

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 4 PAGE 61

For corners in

COMMISSION

ST. JOSEPH

(County)

Located In:

Corner Code #

NOTTAWA TWP.

1. Public Land Survey

T 6S R 10W

M-4

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

STATE OF MICHIGAN  
ST. JOSEPH COUNTY  
FILED

18 OCT 94 2:29 P.M.

CYNTHIA JARRATT  
REGISTER OF DEEDS  
Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, DAVID W. MOSTROM, in a field survey on OCTOBER 5, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(M-4) EAST 1/4 COR. SEC. 12 T6S, R10W

NO EVIDENCE OF GLO WITNESSES

1876 SURVEY - BOOK A, PG. 244

MDOT

STONE

14" Y. OAK = S59°W 60 LINKS

+1D STONE IN MON. BOX

RR ANCHOR POST = N25°E 73.85'

RR ANCHOR POST = WEST 28.75'

COLON TWP COR. = NORTH 66.55'

HWY CL = WEST 3.0'

1974 SURVEY BY PS#14100 &  
LCRC IN BOOK 3, PG 54

BOAT SPIKE IN MON. BOX

GUARD POST = SE 49.7'

RR ANCHOR = NE 88'

ANCHOR POST = WEST 63.9'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.

(M-4)

FOUND BOAT SPIKE IN MON. BOX (NOTHING UNDER BOAT SPIKE)

RR ANCHOR = NE 88'

ANCHOR POST = WEST 63.9'

HWY CL = WEST 3'

RATIFIED BY PEER GROUP  
IN ACCORDANCE WITH P.A. 345  
ON OCT. 10, 1994  
WAM CO. REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(M-4) EAST 1/4 COR. SEC. 12 T6S, R10W

SET 5/8" X 24" IRON BAR W/STD. CAP IN MON BOX

R.R. RAIL ANCHOR POST = N45°E 88.0'

TOP OF IRON GUARD POST = S60°E 49.30'

P. POLE = WEST 71.04'

TOP/CENTER OF CONC. R/W MARKER = S88°W 63.13'

HWY CL = WEST 3'

CORNER IS IN PROJ. OF FENCELINE TO WEST



Signed by

*[Signature]*

Date

OCTOBER 12, 1994

Surveyor's Michigan License No. 32339

# REMONUMENTATION

LIBER 4 PAGE 61