

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Lockport Twp.

St. Joseph (County)	Located in:	Corner Code #
1. Public Land Survey	T 6 S R 11 W	E-8
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

LIBER 6 PAGE 8

STATE OF MICHIGAN
ST. JOSEPH COUNTY
FILED

7 JAN 2000 9:47:53 AM

CYNTHIA L. JARRATT
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Wayne A. Mostrom, in a field survey on 8/3, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1864 Survey in A/65

Stake

15" W.O. - S8°W 23 lks
(15.18')

16" W.O. - N42°E 39 lks
(25.74')

Road Comm. - 1964

Pointed sto. with 1" rod

6" Cherry - North 31.32'

6" Cherry - South 11.18'

8" Blk. Oak - N70°E 66.2'

Pierce 1971 Survey

Sto. & 1 1/4" bar

12" Oak - N65°E 65.83'

4" Cherry - W. 9.77'

8" Cherry - S. 11.43'

Mostrom 1980 Survey

Stone & 1 1/4" bar

12" Oak - N65°E 65.83'

Gove Assoc. 1986 Survey

Fd. stone & Iron bar

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found pointed sto. with 1 1/4" bar along side

in remains of E-W fence

N-S fence = West 4'

RR Tie Post = 51.83'

All Road Comm. wit's check

All Pierce Survey & Mostrom Survey data check

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON AUG. 8, 1999
Way CO. REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Lowered stone & set 5/8" x 24" bar w/std. cap

N & W in E. side 12" Cherry = North 31.32'

N & W in E. side 14" Cherry = South 11.18'

N & W in N. side 26" Oak = N70°E 66.20'

N & W in S. side 12" Cherry = West 9.44'



Signed by Wayne A. Mostrom
Surveyor's Michigan License No. 14100

Date December 30, 1999