

SURVEY &
REMONUMENTATION

SEP 12 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIBER 4 PAGE 334

ST. JOSEPH

Located In:

Corner Code #

(County)

FLORENCE TWP.

1. Public Land Survey

T 7S R 11W

C-11

2. Property Controlling
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

STATE OF MICHIGAN
ST. JOSEPH COUNTY
FILED

18 APR 97 4:57 P.M.

CYNTHIA JARRATT
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, WAYNE A. MOSTROM, in a field survey on MARCH 7, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1889 SURVEY IN A/591

1966 BY ROAD COMM.

1975 LCRC IN 3/129

SAYERS 1984 SURVEY

"STONE SET BY S. LAIRD
OVER 30 YEARS AGO"
SURVEY IN B/523 REFERS
TO THE ABOVE

LONG POINTED STONE
SURROUNDED BY COAL,
BRICK & POTTERY,
RAISED WITH 1/2" PIPE
IN A MON BOX

PIPE IN MON BOX
P.P. = N50°W 45.0'
STOP SIGN = N45°E 43.45'

PIPE IN MON BOX
P.P. = N50°W 45.0'

STREET SIGN =
N45°E 43.45'

RED BRICK SCHOOL = N42°W 50.95'
STL. A.P. = N53°E 50.10' & WOOD A.P. = S45°E 42.8'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 5/8" BAR OVER STONE 28" DEEP
P.O. = N50°W 45.0'

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON April 14, 1997
CO. REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" X 24" BAR W/STD. CAP OVER STONE IN MON. BOX
N & W IN N. SIDE P.P. = N50°W 45.00'
N & W IN N. SIDE P.P. = N75°E 120.82'
CENTER OF STREET SIGN = N60°E 43.45'
SW COR. HSE = N65°E 179.95'
SW COR. BARN = N21°E 207.66'
Q ASPHALT = SOUTH 2'



Signed by Wayne A. Mostrom
Surveyor's Michigan License No. 14100

Date 4/17/97