

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 1 T 42N R 16W	12
	S _____ T _____ R _____	(GCDB 640620)
	S 1 T 42N R 16W	13
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	(GCDB 660620)
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 09/18/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12-Sec. 1) Center-South 1/16 corner, Section 1. Not previously monumented.

(13-Sec. 1) Southeast 1/16 corner, Section 1. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12-Sec. 1) Established the position for the corner midway and on a straight line between Quarter  
corner 1332.52' south and the intersection of 1/4 lines of Sec. 1, 1332.52' north.

(13-Sec. 1) Established the position for the corner at the intersection of straight lines connecting  
opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" W.Birch S66°W 7.53' mrkd "S1/16 BT"  
8" Maple in clump S62°E 11.52' do  
8" B.Spruce N25°E 24.01' do  
7" Cedar N55°W 22.79' do  
E= 8057940.252 N= 142127.911

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
22" W.Pine S43°E 6.01' mrkd "SE1/16 BT"  
15" R.Pine S29°W 28.19' do  
5" R.Pine N28°W 8.47' do  
12" R.Pine N22°E 9.86' do  
E= 8058345.767 N= 142136.583

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID DL6164: N= 131822.939 m. E= 8059239.498 m.

Signed by Stephan J. Szyszkoski Date 02/04/2015  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division