

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 18 T 42N R 16W	SMC North of #4 (GCDB 120476)
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 02/10/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A Witness Corner to the Special Meander corner between Government Lots 2 and 3 on the south shore of the Manistique River. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established the position for the corner on the West 1/16 line, 4 feet south of the apparent ordinary high water mark (as denoted by the vegetation change) on the south shore of the Manistique River. The West 1/16 line is parallel with the N-S 1/4 line of Section 18 and passes through 1/16 corner #4. The distance between 1/16 corner #4 and the monument herein described was determined to be 1016.20'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1"IDx28" I.pipe with 2" aluminum MDNR cap.
SW Bldg. corner S35°E 49.60'
NW Bldg. corner S71°E 38.57'
Set measuring nail with MDNR tag in the side of:
15" Sugar S26°W 70.15' mrkd "SMC BT"
17" Y.Birch S55°W 55.89' do
E= 8068864.775 N= 140113.737



Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID DL6164: N= 131822.939 m. E= 8059239.498 m.

Signed by Stephan J. Szyszkoski Date 04/07/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division