

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 21 T 43N R 15W	5
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 02/08/2011 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(5-Sec. 21) North 1/16 corner, Section 21. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(5-Sec. 21) Established the corner midway and on a straight line between Quarter corner 1326.50' north and Center of Section 21 1326.50' south. The position for the corner falls 11' east of the center of Stutts Creek Road (dirt) and in the vicinity of a two-track easterly.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(5) Set 5/8"x18" rebar with plastic cap stamped MICH DNR LS33986, flush. Set measuring nail with MDNR tag in the side of:
7" R.Pine S75W 16.4' mrkd "N1/16 BT"
8" R.Pine N14W 54.1' do
5" R.Pine N42E 23.85' do
12" R.Pine East 47.05' do
Bearings are magnetic.
Set sq'd post adjacent.



Signed by Stephan J. Szyszkoski Date 02/13/2013
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division