

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
	S 11 T 43N R 16W	4
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File
Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski , in a field survey on Oct. 31 , 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
(4-Sec. 11) Northwest 1/16 corner, Section 11. Not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
(4-Sec. 11) Established the corner at the intersection of straight lines connecting opposite 1/16 corners. 1/16 corners #1 and #5 are monumented by the undersigned. 1/16 corner #3 is computed midway and on line between I3 and I4 as monumented Oct. 25, 2007 by the undersigned and subsequently recorded. 1/16 corner #8 is computed midway and on line between I4 and J4 as recorded by the undersigned.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
(4) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
10" Maple S04E 3.78' mrkd "NW1/16 BT"
19" Y.Birch S51E 10.57' do
4" Maple N37E 9.60' do
13" Beech N68W 33.03' do
Bearings are magnetic.



Signed by Stephan J. Szyszkoski Date 11/14/07

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS