

SURVEY & REMONUMENTATION

NOV 10 1997

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

97 NOV -6 PM 2:37

COMMISSION

For corners in

Shiawassee
(County)

Located in:

Corner Code #

1. Public Land Survey T_6N R_1E M-10
T R
T R
T R
2. Property Controlling S T R
In Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

REGISTER OF DEEDS

Kyle Hubler
SHIAWASSEE COUNTY, MICH.

Register of Deeds Stamp & File Number

I, Mark L. VanRaemdonck, in a filed survey on June 11-13, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1. Original: Joseph Wampler, DS Feb. 1824
Mon: Wood Post
Access: W. Oak 12 N53°W 158
W. Oak 5 S88°W 133
2. Larry Bryan, Cert. Survey, Rec. L. 5, P. 796, 12/2/63
Mon: Set 1/2" Bar & Cap in swale
Set N&T E. face 16" Oak North 103.65'
Set N&T N. face 6" Ash S75°E 36.05'
Set N&T N. face 24" Oak N80°W 98.33'
3. Larry Bryan, L. C. R. C. Rec. L. 2, P. 393 3/7/85
Mon: Set 1/2" Bar & Cap Midway and on line between M-9 and M-11
Access: Set 1/2" Bar & Cap in swale
Set N&T E. face 16" Oak North 103.65'
Set N&T N. face 6" Ash S75°E 36.05'
Set N&T N. face 24" Oak N80°W 98.33'

APPROVED

County Remonumentation
Peer Review Group

*NCC
31 OCT 97*



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found L. Bryan Rerod & Cap as referenced in No. 2 and No. 3. I accepted this location as the careful and faithful re-establishment of the original corner position. Found no conflicting evidence.

C. Description of monument for corner and accessories to perpetuate locating the position of the corner

Removed L. Bryan Rerod & Cap. Offset and installed standard Shiawassee County Harrison Marker stamped, "Remon 24622" at this location. The Marker is witnessed by the following accessories:

North 103.15'	Found N&T #25832 in W. face 24" Oak
S75°E 35.95'	Set N&T 24622 in N. face 12" Ash
N80°W 98.33'	N&T in N. face 24" Oak
North 19.45'	L. Bryan Rerod and Cap
North 2640.24'	Harrison Marker at M-9
South 2640.59'	Harrison Marker at M-11

Signed by *Mark L. VanRaemdonck*

Date *OCT. 29, 1997*

Surveyor's Michigan License No. 24622

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS JAN 18, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

LIBER 1R PG 225