1997 REMONUMENTATION PROGRAM LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 For corners in: COLUMBIA TWP. TUSCOLA Located In: Corner Code # FOR RECORD 1. Public Land Survey T14N R 09E 2. Property Controlling in Section Register of Deeds Stamp & File Number 3. Miscellaneous Property in Sec. CDEFGHIJKLM , Recorded Plat 2 5. Private Claims 6 5 À ż - 2 3 4 7 ġ Ŕ ŧΟ 12 11 i, <u>JONATHAN M. FIELD</u>, in a field survey on <u>JULY 23</u> 19 <u>97</u>, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land 5 δ 18 13 17 16 15 14 7 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a 8 19 20 21 22 23 24 0 Court of Law; established, re-established, monumented, re-monumented, recovered, found as . 27 10 expressed below: 30 29 28 26 25 NOTE: Not more than 4 corners, all in the same town and range, may be recorded 12 3.1 -38 35 36 on this certificate. Description of original monument and accessories and/or subsequent restoration: 1886 TESKEY, C.S.; STAKE PREV. ESTABLISHED; APPLE 4 N29 3/4E 166 1/2LKS.; STAKE N45W 70LKS.

1835 GLO, PARKE, D.S.; SET POST; ELM 17 N17W 25 1/2LKS., ELM 30 N78 1/2E 46LKS.

Description of corner evidence found and/or method applied in restoring or reestablishing corner: 1997 ROWE; FIELD, PS#37276; FND. R.R. SPIKE; ALSO FND. LARGE STONES W/ FRAGMENTS OF WOOD BELOW FND. R.R. SPIKE

4.

ACCEPTED FND R.R. SPIKE AS BEST AVAILABLE EVIDENCE OF ORIGINAL CORNER POSITION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: RÉPLACED FND. RR SPIKE W/ STD. REMON. MONUMENT STAMPED K 13 T14N R9E IN MON. BOX OF MICH

EAST, 10.26' FND. 1/2" ROD APPARENT K-1 T13N-R9E S58°W, 72.21' NAIL W/TAG #11192 IN NE FACE P.POLE (FND NAIL W/TAG) N24°W, 37.86' NAIL W/TAG #11192 IN SE FACE CUT-OFF T.POLE (FND NAIL W/TAG)

N46°E, 80.93' NAIL W/TAG #11192 IN SW FACE P.POLE (FND NAIL W/TAG)

\$63°E, 42.17' CHIS, NOTCH IN E, END 42" CMP

Signed by Surveyor's Michigan License No.

ED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975 REVISED JAN., 1983 ADAPTED FOR WORD PROCESSING MARCH, 1983

JONATHAN

M. FIELD

PROFESSIONAL SURVEYOR No.

של ושעחטט REMONUMENTATION

NOV 2 6 1997

COMMISSION

