SURVEY & REMONUMENTATION

JAN 1 4 1998

Van Buren County Remonumentation Program

Corner Code#

SECTION		
For corners in	Bangor	Township

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970
Section Corner 30,31

(County)	g-i
OD = ADM NAA	
1. Public Land Survey T 2S R 16W A11	DEC 4 34 PH '97
TR	
TR	Mark a South
2. Property Controlling STR	VAN FOUREY DO
in Section S	WER 6 PAGE 26
3. Miscellaneous S TR	Register of Deeds Stamp & File Number
Property in occ.	
4. Lot No, Recorded Plat	A B C D E F G H I J K L M
E Divisto Claims	1 3 2
	2 - 6 - 5 - 4 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5
	3 10 11 12
I Gary C. Bilow in a field survey on 5/28 19 97 do hereby state that under	4 -7 - 8 - 9 - 10 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
requirements of P.A. 74, Michigan P.A. 01 1910, the desired manual of survey instructions of the	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Limited States Department of the interior, bureau at a surface of the michigan	7
that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the tales of the third surveyors or by a Decree of a Court of Law; established, re-established, monumented, Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,	3 19 20 21 22 23 24
recovered, found as expressed below.	
NOTE: Not more than 2 corners, all in the same town and range, may be recorded	10 30 29 28 27 26 25
on this certificate.	1
	12 31 32 33 34 35 36
	13
a Wainut 16, S28°E, 1.27 and a Maple 24, N 7°E, 1.67. Haines measures 39.675 south and a Wainut 16, S28°E, 1.27 and a Maple 24, N 7°E, 1.67. Haines measures 39.675 south and 1930 call for a stone at this corner. In 1937, County Surveyor TA Smith found a stone 4" do 1930 call for a stone at this corner. In 1963, County Surveyor WQ Smith notes "found stone 4.5 and the point of a switch SE 57.0. In 1963, County Surveyor WQ Smith notes "found stone 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up	a red over point. Howard Witnesses N. O. C.
25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron 25, Covert Twp, Surveyor AW Howard reports finding a large point up stone and set an iron bar SE sec25: N, 31.45, W'ly rail; E, 4.7, W'ly rail; S60°E, 65.25, NW cor Toquin store; nole: N45°W, 77.85, face pole found and/or method applied in restoring or reestablishing correscription of come! evidence found and/or method applied in restoring or reestablishing correscription of come! evidence found and/or method applied in restoring or reestablishing correscription of come! evidence found and/or method applied in restoring or reestablishing correscription of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in restoring or reestablishing correct production of come! evidence found and/or method applied in rest	; N45°E, 68.0, face pole; S45°W, 33.3, face ner: Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED
iron bar SE sec25: N, 31.45, W ly fair, E, 4.7, W ly fair, ed. 20. pole: N45°W, 77.85 face pole found and/or method applied in restoring or reestablishing corn Description of come! evidence found and/or method applied in restoring or reestablishing corn A11, Found stone with washing machine crank on east side. Removed stone and set 20" In this GOVERNMENT MONUMENT WAS RESTORED WITH THE APPROVAL OF REMONUMENTATION PEER GROUP OF SURVEYORS AT A MEETING HELD AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE CO. Description of monument for corner and accessories established to perpetuate locating the policy.	Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED ORIGINAL CORNER.
iron bar SE sec25: N, 31.45, W ly rail, E, 4.7, W l	Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED ORIGINAL CORNER. OF MICHOLOGY OF MI
iron bar SE sec25: N, 31.45, Wily fall, E, 4.1, Will fall fall fall fall fall fall fall f	Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED ORIGINAL CORNER. OF MICHOLOGY OF MI
iron bar SE sec25: N, 31.45, Wily Tall, E, 4.7, Will Tall, E, 4.7, Will Tall, E, 4.7, Wily Tall, E, 4.7, Will Tall, E, 4.7, Will Tall, E, 4.7, Will Tall, E, 4.7, Wil	Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED ORIGINAL CORNER. OF MICHOLOGY OF MI
iron bar SE sec25: N, 31.45, W ly fail, E, 4.7, W l	Harrison monument in monument box F THE VAN BUREN COUNTY JUNE 11, 1997, AND IS ACCEPTED ORIGINAL CORNER. OF MICHOLOGY OF MI

FILED