

LI29367PA026

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

\$ 7.00 DEED
DEC 96 1:47 P.M. RECEIPT# 488
RECORDED
FOREST E. YOUNGBLOOD, REGISTER OF DEEDS
WAYNE COUNTY, MI
\$ 4.00 REMONUMENTATION

For corners in

Wayne, Redford Twp.
(County)

Located in:

Corner Code #

1. Public Land Survey

T 1S. R 10E

A-6

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling
in Section

S

S

S

S

3. Miscellaneous
Property in Sec.

S

S

4. Lot No. , Recorded Plat

5. Private Claims

I, William L. Roskelly, in a field survey on Dec 11, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

A-6) West corner section 18, T.1 S., R.10 E., Redford Township

G.L.O. (1830's) Joseph Fletcher set corner post, witnesses: Elm 6N1 E41 (gone), Do 10S11 E49 (gone)
W.P.A. (1930's) set an iron, witnesses: NE 39.72 30" Elm (gone), E 33.00 mon (gone), SE 21.27 42" Maple (gone), SE 61.55 15"
Twin Maple (gone), S 12.38 30" Iron (M=12.40), W 33.00 Mon (gone)
12/22/94 LCRC L. 27796. P. 708 Robert J. Smalley found a concrete monument (with 1/2" bar) in a monument in box, witnesses:
12.39' (M.=12.40) to A-6 Redford Township.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-6) West corner section 18, T.1 S., R.10 E., Redford Township

Found a concrete monument with steel bar in a monument box centerline of Inkster Road (concrete).
Verified corner location by comparing W.P.A. data with field measurements.
A-6 to A-5 Record = 2672.27' Measured = 2671.75' A-6 to A-5 Record = 2655.68 Measured = 2655.03
Angle line A-6 & A-5 to A-6 & A-5 Record = 180°-01'-40" Measured = 180°-01'-31"
LCRC L. 27796. P. 708 Robert J. Smalley found a concrete monument (with 1/2" bar) in a monument in box M-6 12.39'
(M.=12.40) to A-6 Redford Township.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-6) West corner section 18, T.1 S., R.10 E., Redford Township

Found a concrete monument with steel bar in a monument box centerline of Inkster Road (concrete).
The selected location is accepted by the contractor and is generally accepted by professional surveyors as the best available evidence of the position of the corner. WITNESSES: Found P.K. nail, tag #38121 "Spalding Dedecker" top guard rail post M.=S. 47° 14' 58" E 46.34', M.=N. 71° 30' 39" E. 38.14', Found P.K. nail, tag #38121 "Spalding Dedecker" top guard rail post M.=N. 87° 07' 33" W 32.50', Found P.K. nail top guard rail post M.=S. 40° 37' 13" W 46.95', Set nail and W.C.R. tag top guard rail post M.=N. 87° 07' 33" W 32.50'.
Placed Wayne County Remonumentation brass marker and cap #10705.

Signed by

Surveyor's Michigan License No. 10705

Date

12-30-96

