RC 1522

LAND CORNER RECORDATION CERTIFICATE L1277979A685

For corners in	ं	ione of Act 14, month 1	n. 1979
WAYNE	_ Located in:	Corner Code #	
(County)	CITY OF DETROIT		
1. Public Land Survey	T <u>1</u> S R <u>13</u> S TR	023	Compliance with ACT 345, P.A. 1990
	TR		APPROVED ON: 11-21-94 91
2. Property Controlling	TR	***************************************	WAYNE COUNTY REMONUMENTATIO PEER GROUP COMMITTEE
in Section	S T R		I PERCONOL COMMETTEE
3. Miscellaneous Property in Sec.	S T R		Register of Deeds Stamp & File Number
•	3 I	**************************************	
4. Lot No , Rec	orded Plat T LINE PC # 689 AND EAST LI	JU T PRIOV ANDRITO	ਨੌ
O. I IIVate ClaimsWES	I LINE FC # 007 AND EAST LI	LENOX AVENUE	<u> </u>
do hereby certify that under requiren in lines 1 and 2 above were in concurrent manual of survey instruction Management or by a decree of a Colabove were in conformance with the Court of Law; established, re-established below:	n a field survey on <u>NOVEMBER</u> nents of P.A. 74, Michigan P.A. of 1970 nformance with regulations and rule ns of the United States Department of ourt of Law and for that the corner point ne rules of the Michigan Board of Land stablished, monumented, re-monume	O, the corner points mentioned as therefore as required in the of the Interior, Bureau of Land is mentioned in lines 3, 4 and 5 Surveyors or by a Decree of a nted, recovered, found as	128 386 CANFIED WAVENY MACK CHARLEVOIX VERNOR FREUD FREUD 138
NOTE: Not more than 4 come on this certificate.	ers, all in the same town and rang	e, may be recorded	3 2 2 3 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
A. Description of original me	onument and accessories and/or	subsequent restoration:	
NO CORNERS SET IN OR	IGINAL GOVERNMENT SURVEY		ANN STREET
PLATS		*	OF MICHIGAN
L. 27, P. 90 "ST. CLAI	ON PARK" OF THE JEFFERSON PA R PARK SUB'N" A PARK - DETROIT SUBDIVISION"		Ilishing corner:
<u>L.C.R.C</u> . L.27337 P.564 MARTIN C	. DUNN #30081 APRIL 29, 1994		OF OFESSIONAL MINISTER
B. Description of corner ev	idence found and/or method app	lied in restoring or reestable	lishing corner:
FOUND PLASTIC CAP #30	081 ON 1/2" REROD IN 4" DIA. 1 36'	LONG CONCRETE MONUM	IENT.
USING STONE CURB A	STABLISHING R.O.W. LINE OF LEN ND SIDEWALK SPLITS WITH REFE ANY. (LIBER 26, PAGE 91, W.C.R	RENCE TO "JEFFERSON PAI	MONUMENTS, AND ESTABLISHED THE P.C. LINE RK" SUBDIVISION OF THE JEFFERSON
			\$ 13.00 MISCELLANEOUS RECORDING 27 DEC 94 10:56 A.M. RECEIPT# 47A
			RECORDED FOREST E. YOUNGBLOOD, REGISTER OF DEEDS WAYNE COUNTY, MI
PLACED WAYNE COUNT	Y REMONUMENTATION MARKER	LAND ALUMINUM CAP ON E	XISTING CONCRETE MONUMENT.
C. Description of monument	for corner and accessories estat	lished to perpetuate locati	ing the position of the corner:
·	NUMENTATION MARKER AND ALI		
<u>WITNESSES</u>	·		
N.78°W. 68.68' FOUR	ND X IN S.E. BOLT COVER OF L. POL	E ON E. SIDE OF DICKERSON J	JUST N. OF DRIVEWAY GOING INTO APARTMENT COMPLE
	JND TACK IN 2" CHOKE CHERRY 20		
			KERSON 50' N. OF 2 nd HYDRANT NORTH OF ESSEX.
			ON ±20' SOUTH OF DRIVE INTO APARTMENT COMPLEX $_{f}/\mathcal{O}$
THE SELECTED LOCATION FO OF THE POSITION AS			DAS A CAREFUL AND FAITHFUL DETERMINATION
Signed by //////	hillon	Date	12/22/94
Surveyor's Michigan Licer	nse No. <u>30081</u>		