

SURVEY &
REMONUMENTATION

RC 1592

APR 25 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

WAYNE

(County)

Located in: Huron
Township

Corner Code #

1. Public Land Survey

T 4S R 9E

K-13

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

L127800PA659

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 12-7-94
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehouse, in a field survey on October 20 19 94,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-13	1817	G.L.O. Notes	N/A	Post
	1930's	WPA Notes	N/A	Cross
	1974	WCRC Notes	N/A	Iron in Mon. Box
	1980	Cert. Survey Unrecorded	Jekabson	Iron in Mon. Box

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-13 I found 1/2" rebar in a broken box at C/L of Will Carleton Road (concrete) running E-W which agrees with the following witnesses.

Cert. Survey 1980

Tie from NE Cor. Sec. 2 T5S R9E to SE Cor. Sec. 35 T4S R9E West 85.65' r & m

WCRC

Nail S Face MBT Pole NE 56.51' (56.58' m to P.K. on NW Face)

Nail E Face 16" Maple SE 54.89' (54.80' to m Nail w/Tag on W Face)

NW Cor. House #3014 SW 80.54' (80.55' m)

Measures East to L-13 = 2660.78' (G.L.O. = 2640') (WPA = 2661.01')

Measures West to I-13 = 5286.66' (G.L.O. = 5280') (WPA = 5278.66')

Measures West to J-13 = 2635.59' (G.L.O. = 2640') (WPA = 2634.15' & 2633.21' S-35)

Measures North to K-12 = 2634.49' (G.L.O. = 2640') (WPA = 2633.21' S-35 & 2633.33' S-36)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-13 Replaced 1/2" bar with 1/2" rebar and aluminum cap stamped "Wayne Co. Remon." in an existing monument box

P.K. NW Face Util. Pole N 60° E 56.58'

Capped Iron C/L Road (unreadable) S 84° E 85.65'

P.K. N Face 6" Wood Fence Post S 62° E 93.41'

P.K. w/Tag "RLS #10705" W Face 20" Maple S 21° E 54.80'

C/L Top Nut Hyd. N 71° W 142.70'

The selected location is accepted by the Contractor and is generally accepted by professional surveyors as the best available
evidence of the position of the original corner.

Signed by Randy J. Kolehouse

Date 12/14/94

Surveyor's Michigan License No. 25854