

MICHIGAN
DEPARTMENT OF CONSERVATION
FORESTRY DIVISION

LAND CORNER RECORD

T...22 NR...9 W...

-----Wexford-----COUNTY

DESCRIPTION OF CORNER --Section corner common to Sections 2, 8, 17, and 18

DESCRIPTION OF CORNER MONUMENT... 1" x 2 1/4" pipe, below surface of road

WITNESSES TO CORNER -- Double 10" Maple ----- N 40 E ----- 36 links

-- 12" Poplar ----- N 21 W ----- 82 1/2 links

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR
RESTORED.

This corner was established by Forestry Division survey crew while making a partial resurvey of this township. Set corner by double proportionate measurement between corners 1 mile north, 1 mile south, 1/2 mile east, and 1/2 mile west. Could make no conclusive identification of De Voe's corner of record of 1908, which he established somewhat arbitrarily. Corner falls very nearly in line with trails west, north west, and south. Conforms perfectly in longitude considering the measurement ~~ends~~ to the 1/4 and section corners east and west, but is slightly south of the lines generated by said corners for latitude.

Corner was placed and witnessed September 29, 1958.

SURVEYORS SEAL

SIGNED

REGISTERED LAND SURVEYOR

Kenneth J. Oetting
DATE - 10/1/58