

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Wexford

Located In

Corner Code #

(County)

1. Public Land Survey T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
2. Property Controlling  
in Section S 29 T 24N R 11W 8  
S 29 T 24N R 11W 5  
3. Miscellaneous  
Property in Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Craig W. McVean, in a field survey on May, 22 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

8 - None

5 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

8 - CW 1/16 Cor. Section 29 – Set 2" Alum. Cap on 5/8" x 60" rebar in swampy area per standard BLM procedure.

5 - CN 1/16 Cor. section 29 - Set 2" Alum. Cap on 5/8" x 34" rebar per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

8 - CW 1/16 corner section 29  
2" stamped aluminum cap on a 5/8" X 60" Rebar  
N45°W 71.44' to set nail & tag in SW side 18" Cedar  
N72°W 93.89' to set nail & tag in S side 21" Cedar  
N10°E 68.49' to set nail & tag in NW side 8" Cedar  
S10°E 61.79' to set nail & tag in W side 13" Cedar  
Set Blue carsonite post with location tag 1' NE

5 - 2" stamped aluminum cap on the 5/8"X34" rebar  
N66°E 31.00' to nail & tag in N side 6" Ash  
N24°E 19.35' to set nail & tag in E side 14" R. Oak  
N24°W 52.33' to set nail & tag in W side 22" S. Maple  
S32°W 43.62' to set nail & tag in E side 14" B. Cherry  
Set blue carsonite post with location tag 1' NW

Signed by:

*Craig W. McVean*

Date:

*11/16/2003*

Surveyor's Michigan License No.:

39088