

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Wexford

Located In

Corner Code #

(County)

1. Public Land Survey T _____ R _____
T _____ R _____
2. Property Controlling
in Section S 30 T 24N R 11W 5
S 30 T 24N R 11W 6
3. Miscellaneous
Property in Section S _____ T _____ R _____
S _____ T _____ R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on May 13, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

5 - None

6 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

5 - CN 1/16 Cor. Section 30 -
Set 2" Alum. Cap on 5/8" x 34" Rebar per
standard BLM procedure.
CL. N-S 2-track is 4' E.

6 - NE 1/16 Cor. Section 30 -
Set 2" Alum. Cap on 5/8" x 34" rebar per
standard BLM procedure

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5 - 2" stamped aluminum cap on 5/8" X 34" Rebar.
S55°E 42.52' to set nail & tag in S side 10" Cherry
S89°E 33.47' to set nail & tag in N side 13" Elm
N52°E 30.19' to set nail & tag in SE side 3" Cherry
S37°W 47.91' to set nail & tag in W side 4" Cherry
Set Blue carsonite post with location tag 1' NE

6 - 2" stamped aluminum cap on 5/8" X 34" rebar
N26°W 24.45' to nail & tag in NE side 12" S. Maple
N80°E 8.13' to set nail & tag in NW side twin 5" S. Maple
S30°E 9.02' to set nail & tag in NE side 10" S. Maple
S52°W 30.44' to set nail & tag in NW side 4" S. Maple

Signed by:

Craig W. McVean

Date:

11/10/2003

Surveyor's Michigan License No.:

39088