## SURVEY & REMONUMENTATION

)

MAY - 1 1995



RECORDED WASHTENAW COUNTY. MI

JAN 10 9 42 AN 195

## COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	t ming stequi	chieff of Act 1-4, mich. 1 .A. 1	PEGGY M. NAINES COUNTY OLERK/REGISTER
Washtenaw (County)	Located In:	Corner Code ≠≠	-cor-
Public Land Survey     .	T R T R T R	<u>J-11</u>	
2. Property Controlling	\$ T R		LIBER 1 PAGE 255 RM
in Section	S T R		- Copy - Register of Deeds Stamp & File Number
3. Miscellaneous	S T R		Register of Deeds Stamp & File Number
Property in Sec.	S T R	<u> </u>	
4. Lot No , R	ecorded Plat		A B C D E F G H I J K L N
			2 - 6 - 5 - 4 - 3 - 2 - 1 - 1 -
•			3
. Konnoth P. Coloman		10 10 01	4 7 8 9 10 10 11 12-
		-12 . 19 <u>94</u> . of 1970, the corner points mentioned	5
in lines 1 and 2 above were in	conformance with regulations ar	d rules therefore as required in the	6 18 17 17 16 15 14 14 13
current manual of survey instru Management or by a decree of a	ictions of the United States Depar	tment of the Interior, Bureau of Lander points mentioned in lines 3, 4 and 5	8 19 20 21 22 23 24
		of Land Surveyors or by a Decree of a	9   1   20   21   22   23   24
Court of Law; established, re expressed below:	e-established, monumented, re-r	monumented, recovered, found as	10 30 38 37 36 35
•	, all in Atra come towns o		11
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.			12 31 33 33 34 35 36
on this certificate.			13   32   33   34   35   36
A. Description of original r	nonument and accessories and	d/or subsequent restoration:	13 \
See back of sheet	t <b>.</b>		
•			

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found monument 12-14-93 See back of sheet.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the corner and accessories established to perpetuate locating the corner and accessories established to perpetuate locating the corner and accessories established to perpetuate location accessories established to p Found 4" dia. conc. mon. w/ 3/8" bar. Set remonumentation cap. North 136.80 50" Oak West 91.31 8" Hickory, RT, nail N 85° E 18.65 8" Hickory, RT, nail S 05° E 38.65 10" Hickory, RT, nail

Burveyor's Michigan License No.

## J-11 Witness Summary

6-15-1819 J. Wampler D.S. Set 1/4 S. Post at av D.

- 1) Elm 20" N 83 E 8
- 2) D.O 18" S 86 E 13

Midwestern Consulting, Inc. Survey - Job #73392 7-23-73 Found 1" Iron Pipe

- 3) 4.7' N. of Fence to West
- 4) Iron Falls in N-S Fence 5) 36" Stump S 05 E 5.5'

Allen R. Rentschler 1-20-78 W.C.R

Liber 4, Page 398,

Found 1" Iron Pipe

- 3) 4.7' North of fence to West 4) Iron falls in N-S fence 5) 36" Stump, S 05 E, 5.5'

12-14-94 Atwell-Hicks, Inc. Found Monument

- 3) 4.7' N. of fence to west
- 4) Iron falls in N-S fence 5) 36" stump S05°E 5.5'

**APPROVED** DATE 3/8/94 CO. REP.