

# SURVEY & REMONUMENTATION

MAY - 1 1995

COMMISSION

## COPY

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED  
WASHTENAW COUNTY, MI

FEB 1 8 49 AM '95

PEGGY M. BAINES  
COUNTY CLERK/REGISTER

For corners in

WASHTENAW

(County)

Located In:

Corner Code #

1. Public Land Survey

2. Property controlling in Section

3. Miscellaneous Property in Sec.

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

T	4 S	R	4 E	1-12
T		R		
T		R		
T		R		
T		R		
S	T	R		
S	T	R		
S	T	R		
S	T	R		

LIBER

1 PAGE 341 RM

COPY

Register of Deeds Stamp & File Number

I, Paul V. Schwimmer, in a field survey on October 21, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate

A. Description of original monument and accessories and/or subsequent restoration:

Set post in prairie GLO August 31, 1819  
1) W. Oak 10" N 58° W 15 links  
2) W. Oak 14" S 60° E 29 links

Fnd. 1/2" Steel Rod  
3) W. Oak 14" E-S.E. 6.9' to nail and washer  
4) Double W. Oak 30" North 58.3' to nail and washer

Kenneth L. Suydam LS# 17636  
Survey L1 P575  
04/24/1972

Fnd. Re-Rod  
5) Oak 34" N 50° W 128.61' to spike  
4) W. Oak 30" N 05° W 58.25' to nail  
3) W. Oak 14" S 80° E 6.67' to nail

Glenn E. Richards LS# 13040  
Survey L1447 P800  
05/03/1973

B. Description of corner evidence and/or method applied in restoring or reestablishing corner:

Found 1/2" Re-rod 0.20' above ground  
Also found following witnesses set by Suydam and Richards:  
4) 30" Double W. Oak North 58.3' (measured 58.22) to nail  
5) 36" Oak N 50° W 128.61' (measured 128.60) to nail and disc

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Re-set existing 1/2" Re-rod.

Set additional accessories:

6) 30" Oak West 47.02' to PK nail in N side  
7) 7" Oak N 20° E 30.62' to PK nail in N.W. side

I believe this point should be accepted as the best available evidence of the original corner.

Signed by

Paul V. Schwimmer

Date

12/29/94

Surveyor's Michigan License No.

29618

APPROVED

DATE 12/19/94

CO. REP. PA

